CERTIFICATE OF LOCATION OF GOVERNMENT CORNER	
NORTHEAST Corner of Section 32 , Township 143 , Range 25 , 5th P.M.	
STATE OF MINNESOTA, County of <u>CASS</u>	
At the corner location shown on the sketch:	
On found a 2 1/2" ALUMINUM MONUMENT WITH ALUM, CAP SET IN MOUND OF STONE	
■ left monument as found, □ lowered monument, □ removed monument (explain)	
Onplaced a	
NOT TO SCALE SKETCH OF REFERENCE TIES \$\foat{60}{50} 5" BASSWOOD	
₩ NO5W 42.10	
6" BASSWOOD N3OW 34.98	(7) 15" ASPEN (8) N22E 13.53 (1976 BT
-N- 1976 BT	/ 1376 81
	,
``	, ,
MAGNETIC BEARING	MAPLE
4" MAPLE ()- N77W 26.35	N73E 15.67
14" ASPEN	\
574W 49.17 () 1976 BT	, 1
	'\
	``
	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\
	1976 BT T.143N. R.25W. 529 \ 528
8' STEEL SIGN POST 3.00' EAST	532 533
NOTE: ALL BT'S ARE BLAZED, SCRIBED AND PAINTED WITH RED ENAMEL PAINT WITH 1983 BT SIGNS, AND ALL MEASUREMENTS ARE HORIZONTAL TO SPIKE IN SIDE OF TREE CADASTRAL SURVEY BUR, OF LAND MANAGEMENT	
Statement of evidence relative to this corner location is on back of page. $32634/$	
I hereby certify that this document and the data	OFFICE OF THE COUNTY RECORDER
contained herein was prepared by me or under	County of
my direct supervision.	I hereby certify that this document was filed in the Co. Recorders office at 2:30 .M. on the
SIGNATURE DATE	25 day of Anuena A.D., 1991
Registration No. 1/395	County Recorder Clandin Kaylan
☑ Land Surveyor	By M, Deputy
☑ County Surveyor	DOCUMENT NO. 3 & 6 3 9/

Statement of Evidence:

- V-9 NE Cor. of Sec. 32, T. 143 N., R. 25 W.
- 1872 Original survey by Hayward and Griffin, set a wood post and marked bt's as follows; 8" Birch N61E 18 lks
 10" Birch N11W 14 lks
 8" Balsam S22W 20 lks
 8" Sugar S58E 13 lks
- 1924 J.H. Flynn, in making a road survey found the NE, NW, and SE bt's and set a 1" iron pipe monument. recorded in county survey record book D, page 132.
- 1963 USFS made a search for this corner. Book 1, page 9.
- 1976 B.L.M. made a dependent resurvey of part of the township and found a 1" pipe and set a 2 1/2" x 28" aluminum pipe with cap in place of the 1" pipe. They marked bt's as follows; 15" Aspen N22E 20 1/2 1ks 13" Aspen S24E 26 lks 14" Aspen S74W 74 1/2 1ks 6" basswood 53 1ks MOEM
- 1989 The USFS used this monument in a traverse around section 28.
- 1989 Walt Curo found the B.L.M. monument in good condition and accept the B.L.M. monument as being traceable to original position.