

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

West Quarter _____ Corner of Section 31, Township 142, Range 31, 5th P.M.

STATE OF MINNESOTA, County of Cass


At the corner location shown on the sketch:

- On 1/10/91 found a 1 and 1/2 inch iron pipe and original Pine stump
DATE
 - left monument as found, lowered monument, removed monument (explain)
- On 2/9/91 placed a an aluminum cap over 1 and 1/2 inch iron pipe
DATE

Magnetic Decl: 5° East
 Not to Scale

SKETCH OF REFERENCE TIES

All distances are horizontal to nail in side of tree



(1987 BT)
 21" Norway Pine
 N 9 W 89.90'

Monument is located 40'± west of Tamarack swamp on side hill in Pine and Hardwoods.

8' steel sign post North 3.65'.

original Pine stump S 85 E 4.0' (1987 BT)
 7" Tamarack S 80 E 53.25'

All trees are scribed, painted with red enamel and marked with a 54-3 (bearing tree) tag.

Monument Stamped
 T142N
 R32W R31W
 S36+S31
 1991
 RLS 17008

29" White Pine
 S 15 E 18.25'
 (1935 CCC tie)

Statement of evidence relative to this corner location is on back of page. 327277

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.

[Signature] 3/6/91
SIGNATURE DATE

Registration No. 17008

- Land Surveyor, Professional Engineer
- County Surveyor, County Engineer

OFFICE OF THE REGISTER OF DEEDS

County of Cass

I hereby certify that this document was filed in the Reg. of Deeds office at 3:10 P. P.M. on the 11 day of March A.D., 1991

Register of Deeds Claudine Kogler

By [Signature], Deputy

DOCUMENT NO. 327277

West Quarter corner, Section 31, Township 142 North,
Range 31 West, Cass County, Minnesota

X-1 142-31

1871 George Stuntz, U.S. Deputy Surveyor, originally established this corner position while running the West line of Township 142 North, Range 31 West. The notes indicate a wood post was set to mark the corner position and the following witnesses: a 15 inch Yellow Pine South 85 degrees East a distance of 6 links.

1916 Cass County Surveyor's records on microfilm roll 11 S, Book 86, page 18-19 show a survey by F.F. Wilson. The original wood post and Southeast bearing tree were found.

1935 Civilian Conservation Corps, D.J. Sutton, field assistant, found 2 inch County iron pipe in good condition up 14 inches. He places a metal location poster on a 20 inch White Pine South 15 degrees East a distance of 30 links.

1937 Civilian Conservation Corps, Carl Steadland, Foreman, found 2 inch County iron pipe in good condition up 15 inches. He also found the metal location poster as placed by Sutton in 1935.

1987 United States Forest Service personnel find 1 and 1/2 inch iron pipe up 18 inches and original Pine stump South 78 degrees East a distance of 4.0 feet with blaze and scribe visible and the CCC bearing tree now a 29 inch White Pine South 15 degrees East a distance of 18.25 feet. They place a rock ring around pipe and mark new bearing trees: a 21 inch Norway Pine North 9 degrees West a distance of 89.90 feet; and a 7 inch Tamarack South 80 degrees East a distance of 53.25 feet. Corner is 40 feet, more or less, west of Tamarack swamp on side hill in Pine and Hardwoods.

1991 on January 10, a Landecker & Associates, Inc. survey crew find a 1 and 1/2 inch County iron pipe and 1987 USFS tie while traversing west line of the township.

1991 on February 9, a Landecker & Associates, Inc. survey crew place an aluminum cap over the 1 and 1/2 inch iron pipe. Note original Pine stump South 85 degrees East a distance of 3.96 feet. The 1987 USFS bearing trees are in place as shown. A steel sign post was set as noted on front of this certificate.