

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

East Quarter _____ Corner of Section 27, Township 140, Range 27, 5th P.M.


STATE OF MINNESOTA, County of Cass

At the corner location shown on the sketch:

- On _____ found a _____
DATE
- left monument as found, lowered monument, removed monument (explain)
- On 5/9/91 placed a 2" squared tubular monument 36" long with
DATE aluminum cap

Magnetic Decl: 5° East SKETCH OF REFERENCE TIES
Not to Scale

All distances are horizontal to nail in side of tree



 5" Burr Oak
N 40 W 20.65'

 8" (Twin) Red Oak
N 72 E 40.91'

Monument is located 200'± northerly of access road to Stevens Lake in mixed hardwoods

8' steel sign post with Land Survey Monument sign 2.4 feet southerly.

Monument Stamped
T 140 N R 27 W
S27+S26
1991
RLS 17008

 8" Red Oak
S 13 W 73.56'

Statement of evidence relative to this corner location is on back of page. 329224

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.

Alvin A. Lachuk 6/10/91
SIGNATURE DATE

Registration No. 17008

- Land Surveyor, Professional Engineer
- County Surveyor, County Engineer

OFFICE OF THE REGISTER OF DEEDS

County of Cass

I hereby certify that this document was filed in the Reg. of Deeds office at 3:45 P. .M. on the 11 day of June A.D., 1991

Register of Deeds Claudine Koyler
By vr Deputy

DOCUMENT NO. 329224

East Quarter corner, Section 27, Township 140 North,
Range 27 West, Cass County, Minnesota

T - 17

1873 Fendall G. Winston, U.S. Deputy Surveyor, originally established this corner position while subdividing Township 140 North, Range 27 West. The notes indicate a wood post was set and the following bearing trees were marked: an 8 inch Red Oak North 46 degrees 30 minutes West a distance of 20 links; and a 12 inch Poplar North 64 degrees 20 minutes East a distance of 55 links.

November, 1990, a Landecker & Associates of Walker, Inc. survey crew search for corner evidence and found nothing. On May 9, 1991 a Landecker & Associates of Walker, Inc. survey crew make final search for corner, finding no evidence they set a 2 inch squared tubular monument 36 inches long with aluminum cap for the corner up 9 inches at the single proportion position between the Northeast and Southeast corners of Section 27. New bearing trees were marked as shown and a steel sign post set as noted on front of this certificate.

NOTE: See subdivision map on Sheet 2 of 2 of STEVENS LAKE
HOMESITES plat of record.