



Statement of Evidence:

**NORTH QUARTER CORNER SECTION 8, TOWNSHIP 145 NORTH,  
RANGE 31 WEST, FIFTH PRINCIPAL MERIDIAN**

- 1875 The original Public Land Survey was run by Benjamin C. Baldwin. A scribed post was set to mark corner and witness ties were recorded:  
8" Jack Pine N. 63° W. 8 links  
6" Jack Pine S. 28° E. 25 links
- 1906 John Curo set hub for true corner and bearing trees. ( Survey Record Book A, pages 274-275 )  
9" Norway Pine S. 65° W. 28.1 feet  
9" Norway Pine S. 61°24' E. 94.0 feet
- 1914 F.A. Donner found Curo northwest bearing tree and set hub. ( Survey Record Book C, page 92 )
- 1915 Molyneux found Curo's hub pulled out and set new hub. ( Microfilm roll 115, Book 82, page 8, 19 )
- 1915 John Curo set 2 1/4" x 48" iron monument for corner for lost position of north quarter corner. (County Resurvey Plat E-67 )
- 1992 Murray Surveying, Inc., found 2 1/4" x 48" iron pipe under road surface badly bent. Since exact position of iron pipe could not be determined, north quarter corner was established as Curo did at an on line split position.

For information regarding this survey, contact Murray Surveying, Inc., Bemidji, MN.