


CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

East Quarter Corner, Section 2, Township 142 North, Range 26 West,
of the 5th Principal Meridian, Cass County, Minnesota.

July 22, 1997, Northern Lights Surveying & Mapping, Inc. set a brass capped galvanized steel pipe at the single proportioned position between the Northeast & Southeast corners of section 2.

SKETCH OF REFERENCE TIES & EVIDENCE

T142N, R26W



NOT TO SCALE

Bearings are Grid
North Minnesota
Central Zone, measured
with a hand compass
adjusted to 3°E East
declination.

Section 2

Section 1

New bearing trees were
blazed, scribed & painted
red. A tag stating the
bearing & distance was
affixed to the tree. A
nail was placed in the base
of the tree and the distance
was measured from the
monument to the nail.

0.203m Basswood
N20°W
13.754m to 20d nail
in East face
up 0.290m
scribed S2BT
(1997)

0.279m Triple Basswood
S61°W
7.576m to 20d nail
in South face
up 1.198m
scribed S2BT
(1997)

Northeast Corner
Section 2

N0°28'41"E 819.987m


Steel Signpost
East
1.000m
sign54-9
(1997)

Quarter Corner
Galvanized Steel
Pipe
Stamped Brass Cap
(1997)

N0°28'41"E 777.589m

0.254m Maple
S04°E
14.458m to 20d nail
in East face
up 0.372m
scribed S1BT
(1997)

Southeast Corner
Section 2



395044

Statement of evidence relative to this corner location is on the back of this page

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly licensed Land Surveyor under the laws of the State of Minnesota.

LaVerne Leuelling 11-16-97
LaVerne Leuelling Date
Registered Land Surveyor No. 16089
NORTHERN LIGHTS SURVEYING & MAPPING

OFFICE OF THE COUNTY RECORDER
County of Cass

I hereby certify that this document was filed in the Recorder's office.

Time: 2:50 P.M. Date: December 8, 1997
Recorder Claudine Kaylor
By K. S. Deputy
DOCUMENT NO. 395044

Statement of Evidence

East Quarter Corner, Section 2, Township 142 North, Range 26 West,
of the 5th Principal Meridian, Cass County, Minnesota.

1872; General Land Office (G.L.O.) survey notes; Deputy Surveyor E.W. Griffin set a wooden post for the quarter corner and referenced it with the following:

4" Ironwood (0.102m)	5" Spruce (0.127m)
S9°E	S42°W
8 Links (1.609m)	7 Links (1.408m)

Said records are on file with the Secretary of State, St. Paul, Minnesota; handwritten copies of these notes are on file with the United States Department of Agriculture - Forest Service (U.S.D.A.-F.S.) Chippewa National Forest Supervisor's Office, Cass Lake, Minnesota.

November, 1996; Northern Lights Surveying and Mapping, Inc. crew of David Anderson and Joe Foster cruised to the quarter corner position and established two Global Positioning System (G.P.S.) search positions, which were used in a G.P.S. session. The crew noted that the area had been logged and burned; no original evidence was found.

July 22, 1997; Northern Lights Surveying and Mapping, Inc. crew of Foster and Berg monumented the "lost" quarter corner position with a 1.219m long, 0.051m diameter galvanized steel pipe with a 0.063m diameter stamped brass cap, up 0.240m with the following references:

0.254m Maple	0.279m Triple Basswood	0.203m Basswood	Steel Signpost
S04°E	S61°W	N20°W	East
14.458m to 20d nail	7.578m to 20d nail	13.754m to 20d nail	1.000m
in East face	in South face	in East face	sign54-9
up 0.372m	up 1.198m	up 0.290m	
scribed S1BT	scribed S2BT	scribed S2BT	

Northern Lights Surveying and Mapping, Inc. Slater Township Cadastral Survey Book # 72.

Coordinates:

Cass County North:

Northing = 88,330.271 meters
Easting = 174,632.065 meters

State Plane Coordinates
Minnesota Central Zone
NAD 83

Northing = 338,325.065 meters
Easting = 824,759.331 meters

Latitude = 47°08'37.26362" North
Longitude = 93°55'24.92238" West