


CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

Witness Corner to the Meander Corner common to Sections 1 and 12, Township 142 North, Range 26 West, of the Fifth Principal Meridian, Cass County, Minnesota.

On January 29, 1997, Northern Lights Surveying and Mapping, Inc. monumented a witness corner 40 meters westerly of the calculated meander corner relocated at record General Land Office (G.L.O.) distance from the Northeast Corner of Section 11, T.142N., R.26W., and on line to the theoretical proportioned southeast corner of Section 1.

SKETCH OF REFERENCE TIES & EVIDENCE T.142N., R.26W.



NOT TO SCALE

Bearings are Grid North Minnesota Central Zone, measured with a hand compass adjusted to 3°E East declination.

Section 1

Section 12

* 0.203m Black Spruce
N33°W
39.813m to 20d nail
in West face, up 0.582m
Scribed S1BT
(1997)

W.C.M.C.
Aluminum Rod
Monument with
Aluminum Cap
(1997)

40m S89°03'24"E
±83m to lake

Dirty Nose

Calculated Meander Corner


Steel Signpost
West
0.410m
with 54-9 sign
(1997)

* 0.100m Tamarack
S42°E
21.494m to 20dnail
in NE face, up 0.800m
Scribed XX
(1997)

Lake

* 0.127m Tamarack
S09°W
21.702m to 20d nail
in NE face, up 0.800m
Scribed XX
(1997)

New bearing trees were blazed, scribed & painted red. A tag stating the bearing & distance was affixed to the tree. A nail was placed in the base of the tree and the distance was measured from the monument to the nail.



395047

Statement of evidence relative to this corner location is on the back of this page

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly Licensed Land Surveyor under the laws of the State of Minnesota.

LaVerne Leuelling 11-16-97
LaVerne Leuelling Date

Registered Land Surveyor No. 18089
NORTHERN LIGHTS SURVEYING & MAPPING

OFFICE OF THE COUNTY RECORDER
County of Cass

I hereby certify that this document was filed in the Recorder's office.

Time: 2:58 P.M. Date: Dec. 8, 1997

Recorder Claudine Taylor

By K.S. Deputy

DOCUMENT NO. 395047

Statement of Evidence

Witness Corner to the Meander Corner common to Sections 1 and 12, Township 142 North, Range 26 West, of the Fifth Principal Meridian, Cass County, Minnesota.

November, 1872; General Land Office (G.L.O.) survey notes; Deputy Surveyor E.W. Griffin set a wooden post for the Meander Corner and referenced it with the following:

6" Spruce (0.152m)	6" Spruce (0.152m)
S80°W	N06°W
18 Links (3.621m)	18 Links (3.219m)

Said records are on file with the Secretary of State, St. Paul, Minnesota; copies of these records are on file with the Cass County Surveyor's Office, Walker, Minnesota.

November 2, 1996; Northern Lights Surveying and Mapping, Inc. crew chief Foe Foster cruised to the meander corner location and established a search point which was then used as a Global Positioning System (G.P.S.) session point. A search was also conducted at this time, but no G.L.O. evidence was found. A subsequent trip was made to the location a week later, and a calculated meander corner position was searched. The crew found several stumps in the general area, but no conclusive G.L.O. evidence.

January, 1997; Northern Lights Surveying and Mapping, Inc. crew of David Anderson and Joe Foster traversed to the meander corner position established at record G.L.O. distance from the section corner common to Sections 1, 2, 11, and 12, T.142N., R.26W, and on line to the theoretical proportioned southeast corner of Section 1. Due to lack of original G.L.O. evidence, the crew established a witness corner to the meander corner (W.C.M.C.) with a 3.658m long, 0.019m diameter aluminum rod with a 0.083m diameter aluminum cap, up 0.160m, with the following references:

0.203m Black Spruce	0.100m Tamarack	0.127m Tamarack
N33°W	S42°E	S09°W
39.813m to 20d nail	21.494m to 20dnail	21.702m to 20d nail
in West face, up 0.582m	in NE face, up 0.100m	in NE face, up 0.600m
Scribed S1BT	Scribed Xx	Scribed XX

Steel Signpost
West
0.410m
with 54-9 sign

The crew noted that the W.C.M.C. position fell 40m westerly, on line, from the calculated meander corner position. The W.C.M.C. lies in a bog mat southerly of a point of land extending into Dirty Nose Lake.

Northern Lights Surveying and Mapping, Inc. Slater Township Field Book #2, pp.64-66.

Coordinates:

Cass County North

Northing = 87,530.322 meters
Easting = 175,953.098 meters

State Plane Coordinate System
Minnesota Central Zone
NAD 83

Northing = 337,525.640 meters
Easting = 826,080.588 meters

Latitude = 47°08'11.19856" North
Longitude = 93°54'22.37998" West