CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

Meander Corner on the on the north shore of Grave Lake, common to Sections 10 and 11, Township 142 North, Range 28 West, of the Fifth Principal Meridian, Cass County, Minnesota.

June, 1997; Northern Lights Surveying and Mapping Inc. set an aluminum rod at the position of the original General Land Office (G.L.O.) corner post; a Cass County corner post and a 1963 United States Department of Agriculture-Forest Service (U.S.D.A.-F.S.) concrete monument also found at the corner position.



SKETCH OF REFERENCE TIES & EVIDENCE

T.142N., R.26W.

NOT TO SCALE

Bearings are Grid North Minnesota Central Zone, measured with a hand compass adjusted to 3°E East declination. Section 10 | Section 11

Steel Signpost North 1.862m Signs 54-2, 54-9

Steel Signpost West 1.614m

(1997)

Sign 54-9 (1997)

New bearing trees were blazed, scribed & painted red. A tag stating the bearing & distance was affired to the tree. A nail was placed in the base of the tree and the distance was measured from the monument to the pail.

5.182m long Aluminum Rod 0.083m diameter cap (1997)

Meander Corner

Steel Signpost South 1.262m Sign 54-2, 54-9 (1997)

S10 S11" MC
1997
25 18089

Statement of evidence relative to this corner location is on the back of this page

Grane

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that) I am a duly licensed band surveyor under the laws of the State of Minnesota.

LaVerne Leuelling

Registered Land Surveyor No. 16089 NORTHERN LIGHTS SURVEYING & MAPPING OFFICE OF THE COUNTY RECORDER County of

I hereby certify that this document was filed in the Recorder's office.

LZN RZO

395050

in the Recorder's office.

Time: 3:05 P.M. Date: Dec. 8, 1997

Recorder Claudine Kaylor

DOCUMENT NO. 395050

Statement of Evidence

Page 2 of 3 :

Meander Corner on the on the north shore of Grave Lake, common to Sections
10 and 11, Township 142 North, Range 28 West, of the Fifth Principal Meridian, Cass County,
Minnesota.

November, 1872; General Land Office (G.L.O.) survey notes; Deputy Surveyor E.W. Griffin set a wooden post for the meander corner and referenced it with the following:

3" Spruce (0.100m) 5" Tamarack (0.130) N44°E N86°W 10 Links (2.012m) 21 Links (4.224m)

Said records are on file with the Secretary of State, St. Paul, Minnesota; copies of these notes are on file with the Cass County Surveyor's Office, Walker, Minnesota.

1940; United States Department of Agriculture-Forest Service (U.S.D.A.-F.S.) Form 874-9, Chippewa National Forest Civilian Conservation Corps (C.C.C.) Junior Civil Engineer Raymond T. DeFant found a wooden post in fair condition and placed a metal location poster on a fence post. He noted that he believed the wooden post was a monument set by Cass County, but did not indicate a year.

(Form 874-9 on file with U.S.D.A.-F.S. Supervisor's Office, Cass Lake, Minnesota,

1983; U.S.D.A.—F.S. Field Book #2, p.58, on file with the Chippewa National Forest Supervisor's Office, Cass Lake, Minnesota; Survey crew of Okerman, Ekstrom, and McDonald found the original G.L.O. wooden post with "MCS10" and "MCS11" still visible. The crew also found a second post believed to have been a perpetuation of the original corner by Cass County Surveyor J.H. Flynn, in the 1920's. The crew set a 0.152m diameter, 1.524m long cylindrical concrete monument capped with a 0.076m diameter bronze tablet and established the following references:

*0.492m Red Pine Cedar Post Cedar Post/Red Top N54*E Red Top North 72.329m N56*W 1.128m Scribed MCS11BT 1.555m Signs 54-4, 54-2

1964; Affidavit as to Location of Government Corner #283 was filed for the Meander Corner with the Cass County Register of Deeds, Walker, Minnesota, R.LS. #6807. On the Affidavit, William Okerman indicated that the found wooden post was original G.LO. evidence, set in 1872.

1980; U.S.D.A.—F.S. Field Book #2, p.58; Survey Technician Bill Olson cruised to the Meander Corner and found the 1983 monument and references in good condition.

1984; Cass County Index Card on file with Cass County Surveyor's Office, Walker, Minnesota; Cass County survey crew of Freeman and Hummitzch found the 1963 U.S.D.A.—F.S. concrete monument, Red Pine bearing tree and cedar posts, leaning.

November, 1998; Northern Lights Surveying and Mapping Inc. crew of Dave Anderson and Mike Sherek found the 1963 U.S.D.A.—F.S. concrete monument in marginal condition. They pulled distances from existing ties and found that the monument fit the tie distances. The crew tied its position conventionally.

June, 1997; Northern Lights Surveying and Mapping, Inc. crew of Foster, Berg, and Gerving returned to the 1983 concrete monument and found it in poor condition. The crew recovered the orginal G.L.O. wood post and Cass County wood post which were found at the base of the 1963 monument. The crew removed the 1963 monument and set a 5.182m long, 0.019m diameter swamp monument with a 0.083m diameter aluminum stamped cap. The G.L.O. and county wood post were set adjacent to the set monument, east side, 0.200m below mat. The remains of the 1963 concrete monument lies adjacent to the set monument. The 1963 cedar post red tops were still at the corner, but were in very poor condition; therefore, were not referenced. The crew established the following references:

 Steel Signpost
 Steel Signpost
 Steel Signpost

 South
 West
 North

 1.262m
 1.614m
 1.862m

 Sign 54-2, 54-9
 Sign 54-9
 Signs 54-2, 54-9

Statement of Evidence

Page 3 of 3

Meander Corner on the on the north shore of Grave Lake, common to Sections 10 and 11, Township 142 North, Range 26 West, of the Fifth Principal Meridian, Cass County, Minnesota.

Northern Lights Surveying and Mapping, Inc. Slater Township Field Book #1, p.68.

Coordinates:

Cass County North

Northing = 66,134.868 meters Easting = 172,978.768 meters State Plane Coordinate System Minnesota Central Zone NAD 83

Northing = 336,129.13 meters Easting = 823,106.90 meters

Latitude = 47°07'28.37044" North Longitude = 93°58'43.74552" West