

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER


Northeast Corner, Section 22, Township 142 North, Range 26 West, of the Fifth Principal Meridian, Cass County, Minnesota.

June, 1997; Northern Lights Surveying and Mapping, Inc., found and accepted the United States Department of Agriculture-Forest Service (U.S.D.A.-F.S.) bronze capped concrete monument as a perpetuation of the General Land Office (G.L.O.) corner position.

SKETCH OF REFERENCE TIES & EVIDENCE

T.142N., R.26W.

Bearings are Grid North, Minnesota Central Zone, measured with a hand compass adjusted to 3° East declination.



NOT TO SCALE

Section 15

Section 14

0.218m Oak
N69°W
14.948m to 20d nail
in north face, up 0.664m
scribe overgrown
(1963)

0.230m Oak
N58°E
2.714m to 20d nail
in north face, up 0.740m
scribe overgrown
(1963)

Section Corner
Concrete
Monument with
Bronze Cap
(1963)

Steel Signpost
East
0.562m
sign 54-9
(1963)

Bearing Trees were inspected, and BT tags placed as needed. Existing BT nails were upgraded and distances were measured from the monument to the nail.

0.206m Oak
S03°E
23.946m to 20d nail
in west face, up 0.334m
scribe overgrown
(1963)

1mx1m X Rock
S16°W
18.788m
(1963)

Section 22

Section 23



395061

Statement of evidence relative to this corner location is on the back of this page

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly licensed Land Surveyor under the laws of the State of Minnesota.

LaVerne Leuelling 11-16-97
LaVerne Leuelling Date

Registered Land Surveyor No. 18089
NORTHERN LIGHTS SURVEYING & MAPPING

OFFICE OF THE COUNTY RECORDER
County of Cass

I hereby certify that this document was filed in the Recorder's office.

Time: 3:32 P. Date: Dec. 8, 1997

Recorder Claudine Kayler

By K. G. Deputy

DOCUMENT NO. 395061

Statement of Evidence

Northeast Corner, Section 22, Township 142 North, Range 26 West, of the Fifth Principal Meridian, Cass County, Minnesota.

November, 1872; General Land Office (G.L.O.) survey notes; Deputy Surveyor E.W. Griffin set a wooden post for the section corner and referenced it with the following:

| | | | |
|-------------------|-------------------|--------------------|-------------------------|
| 8" Maple (0.152m) | 8" Maple (0.203m) | 10" Maple (0.254m) | 36" White Pine (0.914m) |
| N8°W | S57°W | S60°E | N8°E |
| 7 Links (1.408m) | 13 Links (2.615m) | 33 Links (6.639m) | 23 Links (4.627m) |

Said records are on file with the Secretary of State, St. Paul, Minnesota; copies of these records are on file with the Cass County Surveyor's Office, Walker, Minnesota.

August, 1940; United States Department of Agriculture—Forest Service (U.S.D.A.—F.S.) "Corner of Public Survey" Civilian Conservation Corps (C.C.C.) Form 874-9; on file in Cass Lake, Minnesota; survey crew placed a metal location poster on a 0.127m diameter ASpen, 0.036m and N70°W of a found stake. The crew believed the stake was a Cass County monument, not G.L.O. evidence. The form noted no existing references.

September, 1963; U.S.D.A.—F.S. T.142N, R.26W. Field Book #1, p. 36; Okerman, McDonald, and Ekstrom found a G.L.O. post and a decayed White Pine stump at record bearing and distance. They set a 0.152m diameter, 1.524m long concrete monument for the section corner with a .076m diameter bronze stamped cap. The following references were established:

| | | | |
|---------------|---------------|----------------------|---------------|
| 0.152m Oak | 0.152m Oak | X Rock | 0.152m Oak |
| N69°W | N58°E | 0.076mx0.076mx0.152m | S1°E |
| 14.905m | 2.743m | S20°W | 24.018m |
| Scribed S15BT | Scribed S14BT | 16.764m | Scribed S23BT |

October, 1964; Affidavit #322 filed in Cass County Courthouse, Walker, Minnesota, by William Okerman, RLS #6807 for above work.

January, 1965; Cass County survey crew of Freeman and Hummitzch found the 1963 U.S.D.A.—F.S. monument and references in good condition.

October, 1993; U.S.D.A.—F.S. T.142N., R.26W. Field Book #1, p.36; survey crew Krause and Hayes found the 1963 monument and references in good condition, and used it as a Global Positioning System (G.P.S.) corner position.

October, 1996; Joe Foster of Northern Lights Surveying and Mapping, Inc. found the 1963 U.S.D.A.—F.S. monument in good condition, and used it for a G.P.S. control position.

June, 1997; Northern Lights Surveying and Mapping, Inc. crew of Foster and Gerving returned to the 1963 monument, found it in good condition, up 0.850m, and maintained it and its accessories. They observed the following references:

| | | | |
|--------------------------|-------------------------|--------------|----------------|
| 0.230m Oak | 0.206m Oak | 1mx1m X Rock | Steel Signpost |
| N58°E | S03°E | S16°W | East |
| 2.714m to 20d nail | 23.948m to 20d nail | 16.788m | 0.562m |
| in north face, up 0.740m | in west face, up 0.334m | (1963) | sign 54-9 |
| scribe overgrown | scribe overgrown | | (1963) |
| (1963) | (1963) | | |

0.218m Oak
N69°W
14.946m to 20d nail
in north face, up 0.664m
scribe overgrown
(1963)

No paint was applied to references, a corner was located on private property.

Northern Lights Surveying and Mapping, Inc. Slater Township Field Book #1, p. 38.

Coordinates:

Cass County North

Northing = 64,188.122 meters
Easting = 173,039.040 meters

State Plane Coordinate System
Minnesota Central Zone
NAD 83

Northing = 334,182.50 meters
Easting = 823,167.91 meters
Latitude = 47°08'23.32848" North
Longitude = 93°56'41.20730" West