


CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

North Quarter Corner, Section 24, Township 142 North, Range 26 West, of the Fifth Principal Meridian, Cass County, Minnesota.

July, 1997, Northern Lights Surveying and Mapping, Inc. monumented the Quarter Corner position established on line between the northeast and northwest corners of Section 24 and at record distance from the calculated northeast corner of Section 24.

SKETCH OF REFERENCE TIES & EVIDENCE

T.142N., R.26W.



NOT TO SCALE

Bearings are Grid North, Minnesota Central Zone, measured with a hand compass adjusted to 3° East declination.

Section 13

NW 24

N89°57'25"W
558.891

0.127m Ash
N85°W
7.060m to 20d nail
in north face
up 0.200m
scribed S13BT
(1997)

Steel Signpost
North
0.690m
sign 54-9
(1997)

0.152m Ash
N18°E
15.348m to 20d nail
in east face
up 0.380m
scribed S13BT
(1997)

NE 24

N89°57'25"W
804.674

Quarter Corner
Galvanized
Steel Pipe
Stamped
Brass Cap
(1997)

Section 24

0.102m Ash
S28°W
6.626m to 20d nail
in west face,
up 0.210m
scribed S24BT
(1997)

New bearing trees were blazed, scribed & painted red. A tag stating the bearing & distance was affixed to the tree. A nail was placed in the base of the tree and the distance was measured from the monument to the nail.



395066

Statement of evidence relative to this corner location is on the back of this page

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly licensed Land Surveyor under the laws of the State of Minnesota.

LaVerne Leuelling 11-16-97
LaVerne Leuelling Date

Registered Land Surveyor No. 16089
NORTHERN LIGHTS SURVEYING & MAPPING

OFFICE OF THE COUNTY RECORDER
County of Cass

I hereby certify that this document was filed in the Recorder's office.

Time: 3:45 P.M. Date: Dec. 8, 1997

Recorder Claudine Kayton

By K. J. Deputy

DOCUMENT NO. 395066

Statement of Evidence

North Quarter Corner, Section 24, Township 142 North, Range 26 West, of the Fifth Principal Meridian, Cass County, Minnesota.

1872; General Land Office (G.L.O.) survey notes; Deputy Surveyor E.W. Griffin set a wooden post for the quarter corner and referenced it with the following:

40" White Pine (1.016m)	24" Red Pine (0.610m)
N43°W	S34°E
20 Links (4.023m)	50 Links (10.058m)

Said records are on file with the Secretary of State, St. Paul, Minnesota; copies of these records are on file with the Cass County Surveyor's Office, Walker, Minnesota.

June 4, 1983; United States Department of Agriculture--Forest Service (U.S.D.A.-F.S.) T.142N., R.26W. Field Book #1, p.34; survey technician James Ekstrom chained west from the witness corner common to Sections 13, 18, 19, and 24 and found no evidence of the G.L.O. survey. He noted the area had been badly burned.

November 7, 1986; Northern Lights Surveying and Mapping, Inc. crew of Smith and Berg traversed to a search position calculated as midpoint and on line between the northwest and northeast corners of Section 24. The search area had been logged and showed evidence of being heavily burned. No G.L.O. evidence was found.

July 17, 1997; Northern Lights Surveying and Mapping, Inc. crew of Smith and Gerving monumented the "lost" quarter corner position with a 1.219m long, 0.051m diameter galvanized steel pipe with a 0.003m diameter stamped brass cap, up 0.180m, from which the following references were established:

0.127m Ash	0.102m Ash	0.152m Ash	Steel Signpost
N85°W	S28°W	N18°E	North
7.080m to 20d nail	6.626m to 20d nail	15.348m to 20d nail	0.890m
in north face	in west face,	in east face	sign 54-9
up 0.200m	up 0.210m	up 0.380m	
scribed S13BT	scribed S24BT	scribed S13BT	

Northern Lights Surveying and Mapping, Inc. Slater Township Field Book #3, p.17.

Coordinates:

Itasca County North

Northing = 64,295.10 meters
Easting = 175,412.62 meters

State Plane Coordinate System
Minnesota Central Zone
NAD 83

Northing = 334,290.37 meters
Easting = 825541.33 meters

Latitude = 47°06'26.50898" North
Longitude = 93°54'48.62160" West