


**CERTIFICATE OF LOCATION OF GOVERNMENT CORNER**

North Quarter Corner, Section 25, Township 142 North, Range 26 West, of the Fifth Principal Meridian, Cass County, Minnesota.

June, 1997, Northern Lights Surveying and Mapping, Inc. accepted and monumented R.F. Schneider's 1988 "lost" quarter corner position.

SKETCH OF REFERENCE TIES & EVIDENCE  
T.142N., R.26W.



0.490m Norway Pine (1988)  
N47°W  
34.260m to 20d nail  
in BT face  
blaze visible  
scribed S24

NOT TO SCALE

Bearings are Grid North, Minnesota Central Zone, measured with a hand compass adjusted to 3° East declination.



0.410m Norway Pine (1988)  
N87°W  
30.344m to 20d nail  
in BT face  
blaze visible  
scribed S24

Section 24

Steel Signpost  
West  
1.018m  
sign 54-9  
54-2  
(1997)

Quarter Corner  
Galvanized Steel  
Pipe  
Stamped Brass Cap  
(1997)

Section 25

New bearing trees were blazed, scribed & painted red. A tag stating the bearing & distance was affixed to the tree. A nail was placed in the base of the tree and the distance was measured from the monument to the nail.

0.200m Aspen (1997)  
S13°E  
15.888m to 20d nail  
in NE face  
up 0.500m  
scribed S25BT

395075

Statement of evidence relative to this corner location is on the back of this page

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly Licensed Land Surveyor under the laws of the State of Minnesota.

OFFICE OF THE COUNTY RECORDER  
County of Cass

I hereby certify that this document was filed in the Recorder's office.

Time: 4:07 P.M. Date: Dec. 8, 1997

Recorder Claudine Kaylor

By K.F. Deputy

DOCUMENT NO. 395075

LaVerne Leuelling 11-16-97  
Date  
Registered Land Surveyor No. 16089  
NORTHERN LIGHTS SURVEYING & MAPPING

## Statement of Evidence

North Quarter Corner, Section 25, Township 142 North, Range 26 West, of the Fifth Principal Meridian, Cass County, Minnesota.

November, 1872; General Land Office (G.L.O.) survey notes; Deputy Surveyor E.W. Griffin set a wooden post for the quarter corner and referenced it with the following:

|                         |                    |
|-------------------------|--------------------|
| 20" White Pine (0.508m) | 6" Spruce (0.152m) |
| S38°E                   | N45°W              |
| 40 Links (8.047m)       | 28 Links (5.633m)  |

Said records are on file with the Secretary of State, St. Paul, Minnesota; copies of these records are on file with the Cass County Surveyor's Office, Walker, Minnesota.

1988; Schneider, private surveyor, during a survey of the north half of Section 25, set the quarter corner "lost" between the southeast corner of Section 24 and the recovered meander corner on the east shore of Wilson Lake. (miscellaneous private survey file provided by the United States Department of Agriculture-Forest Service)

Schneider's Ties:

|                          |                          |
|--------------------------|--------------------------|
| 16" Norway Pine (0.406m) | 18" Norway Pine (0.406m) |
| N47°W                    | N67°W                    |
| 112.3 feet (34.229m)     | 99.6 feet (30.358m)      |

November, 1998; Joe Foster of Northern Lights Surveying and Mapping, Inc. cruised 402.337m east of the west sixteenth corner common to Sections 24 and 25, set by Schneider in 1988, to a position and searched for Schneider's quarter corner common to Sections 24 and 25. Not finding the monument, he recovered Schneider's ties and pulled 30.358m at S67°E from the northwest bearing tree. The iron pipe set by Schneider was found lying horizontally under the duff. Foster found the point where the iron pipe had entered the ground, re-set the pipe, and used the pipe as a Global Positioning System (G.P.S.) session position. Schneider's found ties are as follows:

|                 |                 |                                   |
|-----------------|-----------------|-----------------------------------|
| 0.406m Red Pine | 0.406m Red Pine | (the ties were measured to a nail |
| N47°W           | N67°W           | in the base blaze)                |
| 34.229m         | 30.358m         |                                   |

June 5, 1997; Northern Lights Surveying and Mapping, Inc. crew of Foster and Gerving returned to Schneider's quarter corner and monumented its position with a 1.219m long, 0.051m diameter galvanized steel pipe with a 0.083m diameter stamped brass cap, up 0.160m. Schneider's iron pipe was placed on the north side of the set monument; the following references were observed and established:

|                     |                           |                           |                |
|---------------------|---------------------------|---------------------------|----------------|
| 0.200m Aspen (1997) | 0.410m Norway Pine (1988) | 0.490m Norway Pine (1988) | Steel Signpost |
| S13°E               | N67°W                     | N47°W                     | West           |
| 15.686m to 20d nail | 30.344m to 20d nail       | 34.260m to 20d nail       | 1.018m         |
| in NE face          | in BT face                | in BT face                | sign 54-9      |
| up 0.500m           | blaze visible             | blaze visible             | 54-2           |
| scribed S25BT       | scribed S24               | scribed S24               |                |

Northern Lights Surveying and Mapping, Inc. Slater Township Field Book #3, p.1.

## Coordinates:

Cass County North

Northing = 82,639.15 meters  
Easting = 175,390.97 meters

State Plane Coordinate System  
Minnesota Central Zone  
NAD 83

Northing = 232,634.49 meters  
Easting = 825,620.29 meters

Latitude = 47°05'32.89318" North  
Longitude = 93°54'49.95263" West