

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER


Center Quarter of Section 24, Township 142 North, Range 26 West, of the Fifth Principal Meridian, Cass County, Minnesota.

July, 1997, Northern Lights Surveying and Mapping, Inc. monumented the center quarter corner of Section 24 at the intersection of the north-south and east-west quarter lines.

SKETCH OF REFERENCE TIES & EVIDENCE

T.142N., R.26W.

Section 24



NOT TO SCALE

Bearings are Grid North, Minnesota Central Zone, measured with a hand compass adjusted to 3" East declination.

0.188m Red Maple
N17°E
9.592m to 20d nail
in east face
up 0.800m
scribed S24BT
(1997)

0.267m Red Maple
N63°E
23.290m to 20d nail
in NW face
up 0.760m
scribed S24BT
(1997)


Steel Signpost
West
0.900m
sign 54-2
54-9
(1997)

Steel Signpost
East
0.730m
sign 54-2

Center Quarter
Corner
Galvanized
Steel Pipe
Stamped
Brass Cap
(1997)

0.330m Oak
S81°E
17.234m to 20d nail
in north face
up 0.400m
scribed S24BT
(1997)

New bearing trees were blazed, scribed & painted red. A tag stating the bearing & distance was affixed to the tree. A nail was placed in the base of the tree and the distance was measured from the monument to the nail.



400491

Statement of evidence relative to this corner location is on the back of this page

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly Licensed Land Surveyor under the laws of the State of Minnesota.

John Leuelling 5-20-1998
Date

Registered Land Surveyor No. 16089
NORTHERN LIGHTS SURVEYING & MAPPING

OFFICE OF THE COUNTY RECORDER
County of Cass

I hereby certify that this document was filed in the Recorder's office.

Time: 1:00 P. M. Date: June 1st, 1998

Recorder Claudine Kaylor

By K.F. Deputy

DOCUMENT NO. 400491

Statement of Evidence

Center Quarter of Section 24, Township 142 North, Range 26 West, of the Fifth Principal Meridian, Cass County, Minnesota.

July 9, 1997; Northern Lights Surveying and Mapping, Inc. crew of Foster and Sandnas monumented the center quarter position at the intersection of opposite and corresponding quarter corners. They set a 1.219m long, 0.051m diameter galvanized steel pipe with a 0.083m diameter stamped brass cap, and referenced it with the following:

0.188m Red Maple N17°E 9.592m to 20d nail in east face up 0.800m scribed S24BT	0.287m Red Maple N63°E 23.290m to 20d nail in NW face up 0.780m scribed S24BT	0.330m Oak S81°E 17.234m to 20d nail in north face up 0.400m scribed S24BT
---	--	---

Steel Signpost West 0.900m sign 54-2	Steel Signpost East 0.730m sign 54-2 54-9
---	---

Northern Lights Surveying and Mapping, Inc. Slater Township Field Book #3, p.41.

Coordinates:

Itasca County North

Northing = 63,458.69 meters
Easting = 175,401.88 meters

State Plane Coordinate System
Minnesota Central Zone
NAD 83

Northing = 333,453.99 meters
Easting = 825,530.71 meters

Latitude = 47°05'59.42858" North
Longitude = 93°54'49.29397" West