



Statement of Evidence:

NORTH QUARTER CORNER OF SECTION 1, TOWNSHIP 138 NORTH,  
RANGE 32 WEST OF THE FIFTH PRINCIPAL MERIDIAN

The original Public Land Survey was run by Jacob W. Myers in 1860. A post was set to mark the corner and two bearing trees were recorded as accessories; a 7-inch Tamarack South 80 degrees East 24 links, and a 13-inch Tamarack North 68½ degrees West 22 links.

On September 21, 1927, A. R. Taubman, Assistant Hubbard County Engineer, recovered the post and bearing trees recorded by Myers in 1860. A concrete monument measuring 4 inches square at the top, 6 inches square at the bottom and 18 inches long was placed to mark this corner and triangular concrete witness monuments were placed North 52 degrees West 46.669 feet, and North 38 degrees East 46.669 feet.

On October 14, 1993, Todd Larson and Richard Hilliard of the Minnesota Department of Transportation recovered the concrete monument placed by Dahms in 1924 to mark this corner.

The location of this Public Land Survey Corner has been perpetuated by the recovery of the post and placement of the concrete monument by Taubman in 1927 and recovery of the concrete monument by Larson and Hilliard in 1993. An iron spike was placed above the concrete monument to mark this corner.

For additional information and recent survey measurements, contact the Surveys Office of the Minnesota Department of Transportation in Bemidji.