

# CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

Northeast Corner of Section 3, Township 138N, Range 32W, 5TH P.M.

STATE OF MINNESOTA, County of Cass


At the corner location shown on the sketch

ON 1-5-93 found 4"x4" concrete monument

left monument as found,  lowered monument,  removed monument (explain)

placed a

### SKETCH OF REFERENCE TIES



Statement of evidence relative to this corner is on back of page

408857

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.

Kenneth R. Douglas 4-10-97  
SIGNATURE DATE

Registration No. 14950

Land surveyor,  Professional Engineer

County Surveyor,  County Engineer

### OFFICE OF THE COUNTY RECORDER

County of Cass

I hereby certify that this document was filed in the Co. Recorder's office at 1:50 P.M. on the 14th day of January A.D., 1999

County Recorder Claudine Kaylor  
By K.S., Deputy

DOCUMENT NO. 408857

Statement of Evidence:

NORTHEAST CORNER OF SECTION 3, TOWNSHIP 138 NORTH,  
RANGE 32 WEST OF THE FIFTH PRINCIPAL MERIDIAN

The original Public Land Survey was run by Jacob W. Myers in 1860. A post was set to mark the corner and four bearing trees were recorded as accessories; a 3-inch Tamarack North  $43\frac{1}{2}$  degrees West 36 links, a 4-inch Tamarack North 54 degrees East 42 links, a 6-inch Tamarack South  $15\frac{1}{2}$  degrees East 49 links, and an 8-inch Tamarack South 11 degrees West 43 links.

On September 21, 1927, A. R. Taubman, Assistant Hubbard County Engineer, recovered the post and bearing trees recorded by Myers in 1860. A concrete monument measuring 4 inches square at the top, 6 inches square at the bottom and 36 inches long was placed to mark this corner and triangular concrete witness monuments were placed North 37 degrees 30 minutes East 46.669 feet, and South 52 degrees 30 minutes East 46.669 feet.

On October 14, 1993, Todd Larson and Richard Hilliard of the Minnesota Department of Transportation recovered the concrete monument placed by Taubman in 1927 to mark this corner.

The location of this Public Land Survey Corner has been perpetuated by the recovery of the post and placement of the concrete monument by Taubman in 1927 and recovery of the concrete monument by Larson and Hilliard in 1993.

For additional information and recent survey measurements, contact the Surveys Office of the Minnesota Department of Transportation in Bemidji.