

410193

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.

Jamie Kamm SIGNATURE 2/12/99 DATE

Registration No. 23668

- Land Surveyor, Professional Engineer,
- County Surveyor, County Engineer.

OFFICE OF THE COUNTY RECORDER

County of Cass

I hereby certify that this document was filed in the Co. Recorders office at 12:55 P.M. on the 23rd day of February A.D., 1999

County Recorder Claudine Kaylor

By K.F. Deputy

DOCUMENT NO. 410193

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

CENTER SECTION Corner of Section 3, Township 141 N, Range 28 W, 5th P.M.

STATE OF MINNESOTA, County of CASS

At the corner location shown on the sketch:

On 7/16/97 found a GLO MONUMENT UP 1.0 FOOT

left monument as found, lowered monument, removed monument (explain)

On _____ placed a _____



15' MAPLE
COPPER NAIL AND DISK
UP 1.5' NORTH SIDE

25.20'
S 80° W

12' BURR OAK
B.T. TAG
COPPER NAIL AND DISK
UP 1.0' EAST SIDE

7.38'
E 2° N

17.12'
S 10° E

6' ASH
COPPER NAIL AND DISK
UP 1.0' EAST SIDE

23.51'
S 60° E

15' ASH
COPPER NAIL AND DISK
UP 2.0' SW SIDE

Statement of evidence relative to this corner location is on back of page.

Statement of Evidence: Center of section 3, T. 141 N., R. 28 W., 5th P.M.

1921 US General Land Office survey set a 1" x 36" I.P. with a brass cap and marked the following bearings; 8" Elm S 0 1/2 E 102 links, 8" White Oak N 45 W 63 links.

1997 Minnesota Dept. Of Transportation found a GLO monument in good condition and marked the following bearings; 15" maple S 80 W 25.20 ft., 6" Ash S 10 E 17.12 ft., 15" Ash S 60 E 23.51 ft. The Minnesota Department of Transportation accepts this position as the correct location for the corner.

For details and survey analysis, contact The Minnesota Department of Transportation District Surveys Office in Baxter Minnesota.