


CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

East Quarter Corner, Section 32, Township 143 North, Range 27 West, of the Fifth Principal Meridian, Cass County, Minnesota.

On September 11, 1998, Northern Lights Surveying and Mapping, Inc. found and maintained the 1968 United States Department of Agriculture - Forest Service (U.S.D.A.-F.S.) monument and accepted it as a perpetuation of the original General Land Office (G.L.O.) quarter corner.



**SKETCH OF REFERENCE TIES & EVIDENCE
T.143N., R.27W.**

NOT TO SCALE

Bearings are Grid North, Minnesota Central Zone, measured with a hand compass adjusted to 3° East declination.


Soo Line Railroad Grade
218 m ± north of corner

Steel Signpost North
1.722m
(1968)

Steel Signpost East
2.651m
(1968)

Quarter Corner
Concrete filled Galvanized steel pipe with brass cap
(1968)

Steel Signpost South
2.509m
(1968)



Statement of evidence relative to this corner location is on the back of this page

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly Licensed Land Surveyor under the laws of the State of Minnesota.

Joseph Foster 5-21-99
Joseph Foster Date

Licensed Land Surveyor No. 25342
NORTHERN LIGHTS SURVEYING & MAPPING, INC.

OFFICE OF THE COUNTY RECORDER 413185
County of Cass

I hereby certify that this document was filed in the Recorder's office.

Time: 4:30 P.M. Date: May 25, 1999

Recorder Claudine Kaylor

By K.F. Deputy

DOCUMENT NO. 413185

Statement of Evidence

Page 2 of 3

East Quarter Corner, Section 32, Township 143 North, Range 27 West, of the Fifth Principal Meridian, Cass County, Minnesota.

September, 1873; General Land Office (G.L.O.) ; Deputy Surveyor William Allen set a wooden post and referenced it with the following:

7"(0.178m) Spruce	6"(0.152m) Spruce
N 59° W	N30°E
15 Links (3.08m)	11 Links (2.213m)

Said records are on file with the Secretary of State, St. Paul, Minnesota; copies of these records are on file with the Cass County Surveyor's Office, Walker, Minnesota.

April 3, 1903; United States Corps of Engineers survey field book #358, p.13, on file with the National Archives Regional Office, Chicago; during a stadia survey of the township, B.E. Trask found the G.L.O. spruce bearing trees, dead but standing, plainly marked.

Said notes yield computed distances of 805.772 meters and 806.624 meters from the quarter corner to the Southeast and Northeast corners of Section 32, respectively.

1907-1910; A Soo Line track map shows the corner 730 feet (222.5 meters) South of the track centerline. The distance to the Northwest corner of Section 33 was given as 2640 feet (804.674 meters).

1937; John Gjelhaug (RLS #1337) found an original scribed post with no bearing trees at the corner position. Said information is recorded in U.S.D.A.-F.S. T143N, R27W field book #1, p.2.

October, 1940; U.S.D.A.-F.S. Form 874-9; R. DeFant found a post in good condition 40" (1.016m) above ground. He placed a location poster on the post, and noted that the corner fell 10 chains (201.168m) south of the Soo Line Rail Road. He set a pipe alongside the post.

1968; U.S.D.A.-F.S. T143N R27W. Field Book #1, p.2; survey crew under direction of William Okerman RLS 8807, found a scribed post set by Gjelhaug. They set a 2" (0.064m) x 5' (1.524m) long galvanized steel pipe filled with concrete with a 3" (0.076m) brass cap and referenced it with:

Steel Signpost	Steel Signpost	Steel signpost
South	North	East
8.23' (2.509m)	5.65' (1.722m)	8.70' (2.651m)
FS sign 54-4	FS sign 54-2,4	FS sign 54-2,4

December, 1975; Certificate of Location of Government Corner Document #223546 filed by William Okerman, RLS No. 8807, with Cass Co. Recorder, Walker, MN, with the above 1968 information.

September 11, 1998; Northern Lights Surveying and Mapping's crew of Foster and Carlson navigated to the quarter corner position and found the 1968 U.S.D.A.-F.S., monument plumb, in good condition, and up (0.450m). The monument and its accessories were maintained, the following references observed, and the corner position GPS'd for control purposes:

1968 SSP North 1.706m w/54-2 & 54-4
 1968 SSP East 2.620m w/54-2 & 54-9
 1968 SSP South 2.461m w/54-4

Rotted wood post found down; base of post along East side of 1968 U.S.D.A.-F.S., galvanized steel pipe.

Statement of Evidence

Page 3 of 3

East Quarter Corner, Section 32, Township 143 North, Range 27 West, of the Fifth Principal Meridian, Cass County, Minnesota.

Coordinates:

Cass County North

Northing = 70081.011 meters
Easting = 160079.051 meters

State Plane Coordinate System
Minnesota Central Zone
NAD 83

Northing = 340070.083 meters
Easting = 810208.167 meters

Latitude = 47°35.14019" North
Longitude = 94°08'55.47201" West

Northern Lights Surveying and Mapping, Inc. Boy River Township Field Book #4,
Pp. 34 & 35.