


### CERTIFICATE OF LOCATION OF GOVERNMENT CORNER


Meander Corner common to Section 1, Township 141 North, Range 30 West and Section 6, Township 141 North, Range 29 West, of the Fifth Principal Meridian, Cass County, Minnesota. This corner was accepted as a direct perpetuation of the original GLO Meander Corner.

#### SKETCH OF REFERENCE TIES T 141 N, R 29-30 W



NOT TO SCALE

New bearing trees were blazed, scribed and painted red. A location tag was affixed to the tree. A 60d spike was placed in the tree and the horizontal distance was measured from the monument to the spike.



Leech Lake

1"x36" iron pipe with GLO brass cap up 2.2' with an 8' steel sign post wired to it.

T001

8' steel sign post 4.6' South.

9 1/2" Balsam S58°W 39.25' to 60d spike in NW face up 1.2'

S58°W 39.25'

Section 1

S43°W 168.60'

Section 6

12" Basswood S43°W 168.60' to 60d spike in NW face up 1.7'

S02E 207.15'

7" Basswood S02E 207.15' to 60d spike in West face up 1.7'

Bearings are Grid North, Minnesota Central Zone, measured with a hand compass adjusted to 3° East declination.

Abstract Document #480056

Statement of evidence relative to this corner location is on the back of this page

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly Licensed Land Surveyor under the laws of the State of Minnesota.

*LaVerne Leuelling*  
LaVerne Leuelling Date 2-11-04  
Licensed Land Surveyor No. 16089  
Northern Lights Surveying & Mapping, Inc.

OFFICE OF THE COUNTY RECORDER  
County of Cass

I hereby certify that this document was filed in the Recorder's office.

Time: 9:05 A.M. Date: February 12, 2004  
Recorder Kathryn M. Nyby  
By thv Deputy  
DOCUMENT NO. 480056

## Statement of Evidence

Page 2 of 2

Meander Corner common to Section 1, Township 141 North, Range 30 West and Section 6, Township 141 North, Range 29 West, of the Fifth Principal Meridian, Cass County, Minnesota.

1873: General Land Office (G.L.O.) survey notes. P. H. Conger, Deputy Surveyor, set wood post for the corner and referenced it with the following:

11" Cedar	7" Cedar
S6 1/2°E	S13°W
23 lks (15.18')	47 lks (31.02')

Said notes are on file with the Secretary of State, St. Paul, Minnesota. Copies of these notes are on file with the Cass County Surveyor's Office, Walker, Minnesota.

1917: Earl G. Harrington, US Surveyor, found the original MC which was a decayed wooden stake with markings obliterated and remains of the original BT's. He set a 1"x36" iron pipe with a brass cap from which he made the following BT's:

6" Birch	10" Oak
S0°30'E	S35°W
431 lks (284.46')	271 lks (178.86')

Notes of GLO Resurvey of 1918, page 178. Said notes are on file with the Secretary of State, St. Paul, Minnesota. Copies of these notes are on file with the Cass County Surveyor's Office in Walker, Minnesota.

January 18, 2000: R Main, United States Forest Service, found the GLO iron in place tipped over. He straightened the iron and drove an 8' steel sign post along the iron and wired it to the sign post. Iron and post were 6" above ground. Witnessed with an 8' steel sign post 4.6' South. USFS Book 3, Page 52.

December 3, 2003: A Northern Lights Surveying & Mapping crew consisting of Jeff Major and Brad Thompson found the 1" brass capped iron rod tied to the sign post and accepted it as a direct perpetuation of the original GLO Meander Corner. The following new bearing trees were established, each with a location tag. Each tree was blazed, scribed and appropriately painted. The original copy of the notes are on page 10, Book 2 for contract No. 53-6392-3-2 and are on file at the Supervisor's Office of the Chippewa National Forest in Cass Lake, Minnesota. Copies are in the office of Northern Lights Surveying & Mapping in Grand Rapids, MN.

9 1/2" Balsam	12" Basswood	7" Basswood
S58°W	S43°W	S02°E
39.25' to 60d spike in NW face up 1.2'	168.60' to 60d spike in NW face up 1.7'	207.15' to 60d spike in West face up 1.7'

## Coordinates by Static GPS:

State Plane Coordinate System  
Minnesota Central Zone  
NAD 83 (HARN 96)

Y = 1,081,297.18'  
X = 2,585,874.87'

## Cass County North

Northing = 195,537.33'  
Easting = 452,898.03'

## Geodetic Coordinates:

Latitude = 47° 03' 55.3614"N  
Longitude = 94° 24' 20.9429"W