


CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

North 1/16th Corner common to Section 1, Township 141 North, Range 30 West and Section 6, Township 141 North, Range 29 West, of the Fifth Principal Meridian, Cass County, Minnesota. This 1/16 corner is accepted as an indirect perpetuation of the 1/16 corner originally set by the GLO Resurvey and Subdivision of 1917. The 1/16 corner was reset by Walter Curo in 1981 from original evidence.

SKETCH OF REFERENCE TIES T 141 N, R 29-30 W



NOT TO SCALE

8" Red Oak
N52°W
17.76' to 16 d nail in
South face up 1.3'
1981

8' Steel fence post
N2°E 2.77'
up 5.44' with
54-2 and 54-9 signs

2"x36" iron pipe with
brass cap up 1.0'

Section 6

8' Steel fence post
N88°W 3.64'
up 5.80' with
54-2 and 54-9 signs

8' Steel fence post
S12°W 3.14'
up 5.70' with
54-9 sign

13" Red Oak
S77°E
60.30' to 16 d nail in
North face up 0.6'
1981

Section 1

11" Red Oak
S18°W
41.31' to 16 d nail in
West face up 1.0'
1981

Bearings are Grid
North, Minnesota
Central Zone, measured
with a hand compass
adjusted to 3° East
declination.

Abstract Document
#480057

Statement of evidence relative to this corner location is on the back of this page

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly Licensed Land Surveyor under the laws of the State of Minnesota.

LaVerne Leuelling
LaVerne Leuelling
2-11-04
Date
Licensed Land Surveyor No. 16089
Northern Lights Surveying & Mapping, Inc.

OFFICE OF THE COUNTY RECORDER
County of Cass

I hereby certify that this document was filed in the Recorder's office.

Time: 9:10 A.M. Date: 2-12-2004
Recorder Kathryn M. Deby
By HV Deputy
DOCUMENT NO. 480057

Statement of Evidence

Page 2 of 2

North 1/16th Corner common to Section 1, Township 141 North, Range 30 West and Section 6, Township 141 North, Range 29 West, of the Fifth Principal Meridian, Cass County, Minnesota.

1917: Earl G. Harrington, US Surveyor, set a 1"x36" iron pipe with a brass cap from which he made the following BT's:

16" Pine	16" Oak
N48 1/2°W	S29 1/4°E
70 lks (46.20')	51 lks (33.66')

Notes of GLO Resurvey of 1917, Page 163. Said notes are on file with the Secretary of State, St. Paul, Minnesota. Copies of these notes are on file with the Cass County Surveyor's Office, Walker, Minnesota.

September 14, 1981: Walter E. Curo and Paul Johnson found no monument. It was taken out by construction. They found the remains of the Pine BT with legible scribing. They measured from the Pine BT and set a point, then measured S40°E 33.6' and found a hole where a tree had rotted away. They set a 2"x36" iron pipe with a brass cap from these ties and made the following BT's:

8" Red Oak	8" Red Oak	10" Red Oak	8" Steel Sign Post
N51°18'W	S18°21'W	S79°16'E	South
17.68'	41.35'	60.15'	3.0'

Certificate of Location of Government Corner by Walter Curo filed in Cass County as Doc. No. 262631 dated 12/8/81.

January 31, 2000: R. Main, United States Forest Service, found the monument and added two new Sign Posts. USFS Book 3, Page 51.

8' Steel Sign Post	8' Steel Sign Post
North	West
2.7'	3.5'

September, 2003: Northern Lights Surveying and Mapping, found the monument and sign posts in good condition. The following BT's were found and painted:

11" Red Oak	8" Red Oak	13" Red Oak
S18°W	N52°W	S77°E
41.31' to 16 p in	17.76' to 16 p in	60.30' to 16 p in
West face up 1.0'	South face up 1.3'	North face up 0.6'

The original copy of the notes are on pages 16 & 70, Book 1 for USFS contract No. 53-6392-3-2 and are on file at the Supervisor's Office of the Chippewa National Forest in Cass Lake, Minnesota. Copies are in the office of Northern Lights in Grand Rapids, MN.

Coordinates by Static GPS:

Cass County North

Northing = 194,461.522
Easting = 452,863.230

State Plane Coordinate System
Minnesota Central Zone
NAD 83 (HARN 98)

Y = 1,080,221.40'
X = 2,585,840.56'

Geodetic Coordinates:

Latitude = 47° 03' 44.7428"N
Longitude = -94° 24' 20.8080"W