

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly Licensed Land Surveyor under the laws of the State of Minnesota.

Terry L. Freeman
 TERRY L. FREEMAN

Date: 8/26/05 License No: 21367

OFFICE OF THE COUNTY RECORDER
 County of CASS

I hereby certify that this document was filed in the Office of the County Recorder at _____ o'clock _____ M. on the _____ day of _____, 20____ A.D.

County Recorder _____
 By: _____, Deputy
 DOCUMENT NO. _____

EAST QUARTER Corner of Section 9, Township 139, Range 30, 5TH P.M.

On 3/28/05 found a 1 1/2 INCH IRON PIPE DOWN ±4 INCHES

left monument as found, lowered monument, removed monument (explain)

On _____ placed a _____

decl: 5° EAST (ASSUMED)


SKETCH OF REFERENCE TIES

INDEX NO. G-13

Not to Scale



5" OAK



N 78° W
16.99

S 66° E
1.35

POWER POLE

29±

CENTERLINE TOWNSHIP ROAD

15" OAK



S 30° W
45.71

ALL DISTANCES ARE HORIZONTAL TO NAIL IN BASE OF BEARING TREE.

Statement of evidence for this corner position is on the back of this page

STATEMENT OF EVIDENCE

Index No. G - 13

East Quarter Corner, Section 9, Township
139 North, Range 30 West, Cass County,
Minnesota

- 1865 George B. Wright and Thomas B. Walker, U.S. Deputy Surveyors, originally established this corner position while surveying the subdivisions and meanders in Township 139 North, Range 30 West. A wood post was set for the corner position with the following witnesses: A 20 inch Norway Pine, South 81 degrees East, 72 links; A 20 inch Norway Pine, North 1 degree 45 minutes West, 55 links.
- 1976 Roger Mustonen, R.L.S. #11946, found an iron pipe while surveying plat of Stellötto. He accepts it as the corner position.
- 1999 Bruce Grivna, R.L.S. #17253, certificate of survey shows a found iron monument.
- 2005 A Landecker and Associates, Inc. survey crew found a 1 1/2 inch iron pipe down ± 4 inches and accepts it as the position for the East Quarter corner of Section 9. The following accessories were established: A 5 inch Oak, North 78 degrees West, 16.99 feet; A 15 inch Oak, South 30 degrees West, 45.71 feet; A Power Pole, South 66 degrees East, 1.35 feet.

A000505016

**OFFICE OF COUNTY RECORDER
CASS COUNTY MINNESOTA**

**CERTIFIED, FILED, AND/OR
RECORDED ON
10/11/2005 12:37:58PM**

**AS DOC #: A000505016
PAGES: 2
REC FEES: \$0.00**

**KATHRYN N. NORBY
COUNTY RECORDER**

BY Kathryn Norby **DEPUTY**
+V