A000516676

OFFICE OF COUNTY RECORDER CASS COUNTY MINNESOTA

CERTIFIED, FILED, AND/OR RECORDED ON 08/16/2006 12:39:14PM

AS DOC #: A000516676 PAGES: 2 REC FEES: \$0.00

> KATHRYN M. NORBY COUNTY RECORDER

SPIKE IN EP NW FACE. UP 1 FOOT 45.58 FEET N 40° E -7' +/-TH. 87 TH. 87 SPIKE IN TPED POST SE FACE, UP 2 FEET A VE. 44.90 FEET S 38° W -O- SPIKE IN EP SW FACE, UP 1.5 FEET 48 TH 54.83 FEET S 47° E 6 S&W = 6" SPIKE AND WASHER N&W = ROOFING NAIL AND WASHER

Statement of evidence for this corner location is on back of this page.

I hereby certify that this document was researched and prepared by me or under my direct supervision.

Signature South La

3/14/06

License No. 42619

Title: X Land Surveyor

☐ Professional Engineer

☐ County Surveyor

County Engineer

<u>Statement of Evidence:</u> East Quarter Corner of Section 1, Township 138, Range 31 West, 5th Principle Meridian, Cass County Minnesota.

The Original Government Survey was run in 1865 and a post was set to mark the corner. Bearing ties were made to two Black Pine trees.

In 1921, Mr. E.B. Horst recovered a cast iron monument in place as well as the bearing ties.

In 2006 Kramer Leas DeLeo recovered a 2" capped pipe and bearing tree ties were made to a post and two power poles. Kramer Leas DeLeo accepts this as the correct location for the corner.

For details and survey analysis contact Kramer Leas DeLeo in Brainerd, Minnesota.