A000549056

OFFICE OF COUNTY RECORDER CASS COUNTY MINNESOTA

CERTIFIED, FILED, AND/OR RECORDED ON 05/12/2009 03:29:30PM

AS DOC #: A000549056

PAGES: REC FEES: \$0.00

License Number

☐ County Surveyor

KATHRYN M. NORBY COUNTY RECORDER

V-9 Index No. CERTIFICATE OF LOCATION OF GOVERNMENT ,Range <u>27 W</u> NORTHEAST _____ Corner of Section 32 Township 140 N CASS 5TH Principal Meridian, State of Minnesota, County of At the corner location shown on the sketch: . found a . On _ ☐ left monument as found, □ lowered monument, □ removed monument (explain) On 1/12/09 Placed a 3/4" X 24" REBAR WITH SURVEY CAP STAMPED "MN DNR LS 44974" UP 0.2' SET DNR RP UP 1' EAST SIDE 18" RED PINE wooded SET DNR RP UP 0.2' SOUTH SIDE wooded 16" RED PINE 29 28 N 75° W 1.59' 32 33 wooded NORTH ZONE SET DNR RP CASS COUNTY UP 1' NORTH COORDINATE SYSTEM SIDE 8" OAK NAD 83 1996 ADJ. N = 137099.434NOT TO SCALE E = 525969.682BEARINGS OBSERVED WITH A COMPASS RAL JANUARY 2009 Statement of evidence for this corner location is on back of this page. I certify that this document was researched and prepared by me or under my direct supervision. DATE 4 44974

Professional Engineer

SIGNATURE

Land Surveyor

Title:

☐ County Engineer

STATEMENT OF EVIDENCE

Northeast Corner Section 32, Township 140 North, Range 27 West, 5th P.M.

The Department of Natural Resources, Division of Lands and Minerals, contacted the following offices for information regarding this corner:

MN Secretary of State Cass County Recorder Cass County Surveyor Landecker & Associates Inc. Washburn Lake DNR Forestry

1873 The US General Land Office field notes, on file in the Secretary of State's Office, indicate a post set at the corner with the following bearing trees:

20" W. Pine	S 49° W	43 Links (28.38')
20" W. Pine	N 43° W	23 Links (15.18')
5" Balsam	N 62° E	24 Links (15.84')
14" W. Pine	S 60° E	24 Links (15.84')

- 1938 Civilian Conservation Corps field notes Book 9, page 14, located at Washburn Lake DNR Forestry office indicate a post set at the approximate corner location.
- In September, the DNR survey crew searched for evidence of the corner but found nothing.
- In January, the DNR survey crew returned to the area and again found no evidence of the corner. The corner was determined lost and established by double proportion measurement from the Northeast corner of Section 29, the Northeast corner of Section 31, the Southeast corner of Section 32 and the Northeast corner of Section 33. A 3/4" x 24" rebar with plastic cap stamped "MN DNR LS 44974" was set to mark the corner.

The Northeast corner of Section 29 bears N 01°14'09" W 5271.48' The Northeast corner of Section 31 bears N 89° 49' 11" W 5261.14' The Southeast corner of Section 32 bears S 00°27'36" W 5271.48' The Northeast corner of Section 33 bears S 89° 46'49" E 5247.97'

For more information on our survey in this area, please contact the MN DNR, Division of Lands and Minerals, Survey Section, 1601 Minnesota Drive, Brainerd, MN 56401

PAGE 2 OF 2 PAGES