Form	349

CHAPTER 359 LAWS OF 1921



CERTIFICATE OF	LOCATION OF	GOVERNMENT CORNER
36	140 North	27 West
Corner to Sec. 31	T. 140 North	R. 26 West
Collect to Door		

I hereby certify that on 2 nd day of T140N R27W 1,19 40 I found the one-quarter Corner to Sec. 31 T140N R26W which was evidenced by All evidence lost but I re-established the corner. (See below) and I further certify that to perpetuate the location of such corner I did at the exact location thereof place a perment marker consisting of an 1-½" iron pipe. 4-½" long. capped and stamped. I further certify that I established two bearing trees for reference or witness monuments consisting of an 8" Tamarack and a 12" Jack Pine. which reference or witness monuments are located in the manner following: Tamarack 8" N 39 E 20.3Feet Jack Pine 12" N 19½ W 130.8 Feet. To locate this corner I started south from the accepted iron pipe corner to Sec. 25 & 36 T 140 N R 27 W and Sec. 30 & 31 T 140 N R 26 W - Set by County Surveyor Green in 1924 - on a line bearing S 6 % and ran four miles to the accepted from pice corner for Sec. 13 & 24 T 139 N R 27 W and Sec. 18 & 19 T 139 N R 26 W - Set Deputy County Surveyor H. S. Todd - setting a temporary corner on the ice on Lake George for the cerner to Townships 139 & 140 North Ranges 26 & 27 West. Then I started East from the accepted corner to Sec. 35 & 36 T 140 N R 27 W and Sec. 1 & T 139 N R 26 W - set by Deputy County Surveyor H. S. Todd and 1913 from original started East from the accepted corner to Sec. 35 & 36 T 140 N R 27 W and Sec. 1 & T 139 N R 26 W - set by Deputy County Surveyor Green - on a line bearing N 84 K and ran the iron pipe ½ corner Sec. 31 T 140 N R 26 W and Sec. 6 T 139 N R 26 W - set by Deputy County Surveyor Green - on a line bearing N 84 K and ran the iron pipe ½ corner Sec. 31 T 140 N R 26 W and Sec. 6 T 159 N R 26 W - set by Deputy County Surveyor Green - on a line bearing N 84 K and ran the iron pipe ½ corner Sec. 31 T 140 N R 26 W and Sec. 6 T 159 N R 26 W - set by double proportion I located the corner to Townships 139 & 140 North Ranges 27 West. Then by single proportion I located the ½ corner to Sec 36 T 140 N R 26 W and Townships 139 & 140 North R	State of Minnesota	1					
I hereby certify that on 2 nd day of 36 T140N R25W I found the ens-quarter Corner to Sec. 31 T140N R25W which was evidenced by All swidence lost but I re-established the corner. (See below) and I further certify that to perpetuate the location of such corner I did at the exact location thereof place a pern nent marker consisting of an 1-½" iron pipe, 4-½" long, capped and stamped. I further certify that I established two hearing trees for reference or witness monuments consisting of an 8" Tamarack and a 12" lack Pine. which reference or witness monuments are located in the manner following: Tamarack 8" N 59 E 20.3Feet Jack Pine 12" N 19½ W 150.8 Feet. To locate this corner I started south from the accepted iron pipe corner to Sec 25 & 36 T 140 N R 27 W and Sec. 30 & 31 T 140 N R 26 W - Set by County Surveyor Green in 1924 on a line bearing S 6 % and ran four miles to the accepted rorn pic corner for Sec. 13 & 24 T 139 N R 27 W and Sec. 18 & 19 T 159 N R 26 W - Set be Deputy County Surveyor H. S. Todd - setting a temporary corner on the ice on Lake George for the corner to Townships 139 & 140 North Ranges 26 & 37 West. Then I started East from the accepted corner to Sec. 35 & 36 T 140 N R 27 W and Sec. 1 19 N R 28 W - Set by Deputy County Surveyor H. S. Todd and 1913 from original evidence and relocated by County Surveyor Green - setting a temporary corner to the four townships on the 10 By double preportion I located the corner to Townships 139 & 140 North Ranges 26 West. Then by single proportion I located the corner to Sec. 36 T 140 N R 28 W and Sec. 31 T 140 N R 26 W - set by County Surveyor Green - setting a temporary corner to Sec 36 T 140 N R 28 W - set by County Surveyor Green - setting a temporary corner to Sec 36 T 140 N R 28 W - set by County Surveyor Green - setting a temporary corner to Sec 36 T 140 N R 28 W - set by County Surveyor Green - setting a temporary corner to Sec 36 T 140 N R 28 W - set by County Surveyor Green - setting a temporary corner to Sec 36 T 140 N R 28 W - set by County	•	ss.			•		
which was evidenced by All evidence lost but I re-established the corner. (See below) and I further certify that to perpetuate the location of such corner I did at the exact location thereof place a pern ment marker consisting of an 1-½" iron pipe. 4-½" long, capped and stamped. I further certify that I established two bearing trees for reference or witness monuments consisting of an 8" Tamarack and a 12" Jack Pine. which reference or witness monuments are located in the manner following: Tamarack 8" N 39 E 20.3Feet Jack Pine 12" N 19½ W 130.8 Feet. To locate this corner I started south from the accepted iron pipe corner to See 25 & 36 T 140 N R 27 W and Sec. 30 & 31 T 140 N R 26 H - Set by County Surveyor Green in 1924 - on a line bearing 5 & W and ran four miles to the accepted iron pi corner fer Sec. 15 & 24 T 139 N R 27 W and Sec. 18 & 19 T 139 N R 26 W - Set 1 Deputy County Surveyor H. S. Tedd - setting a temporary corner or the ice on Lake George for the cerner to Townships 139 & 140 North Ranges 26 & 27 West. Then I started East from the accepted corner to Sec. 35 & 36 T 140 N R 27 W and Sec. 1 A T 139 N R 27 W - Set by Deputy County Surveyor R. S. Todd and 1915 from original evidence and relocated by County Surveyor Green - on a line bearing M 84 R and ran the iron pipe 1 corner Sec. 31 T 140 N R 26 W and Sec. 6 T 139 N R 26 W - set by double preportion I located the corner to Townships 139 & 140 North Range 27 We and Townships 139 & 140 North Ranges 26 West. Then by single proportion I located the 1 corner to Sec 36 T 140 N R 26 W - set 1 Dated at Outing Minn, this day of January Office of Register of Deeds County Surveyor Creen - setting a temporary corner te the four townships 139 & 140 North Range 26 West. Then by single proportion I located the 2 corner to Sec 36 T 140 N R 27 Wend Sec. 31 T 140 N R 26 W - on the selection of the set of the second of th				5 5			10.40
which was evidenced by All evidence lost but I re-established the corner. (See helew) and I further certify that to perpetuate the location of such corner I did at the exact location thereof place a pern nent marker consisting of an 1-2" iron pipe, 4-2" long, capped and stamped. I further certify that I established two bearing trees for reference or witness monuments consisting of an 8" Tamarack and a 12" Jack Pine. Which reference or witness monuments are located in the manner following: Tamarack 8" N 39 E 20.3Feet Jack Pine 12" N 19½ W 150.8 Feet. To locate this corner I started south from the accepted iron pipe corner to Sec 25 & 36 T 140 N R 27 W and Sec. 30 & 31 T 140 N R 25 W - Set by County Surveyor Green in 1924 - on a line bearing 8 6 % and ren four miles to the accepted iron pipe corner fer Sec. 15 & 24 T 139 N R 27 W and Sec. 18 & 19 T 139 N R 26 W - Set lognery County Surveyor H. S. Todd - setting a temporary corner on the ice on Lake Coerge for the cerner to Townships 139 & 140 North Ranges 26 & 27 West. Then I started East from the accepted corner to Sec. 35 & 36 T 140 N R 27 W and Sec. 18 % T 139 N R 27 W - Set by Deputy County Surveyor Green - on a line bearing M 84 K and ran the iron pipe 1 corner Sec. 31 T 140 N R 26 W and Sec. 6 T 139 N R 26 W - set by M double preportion I located the corner to Townships 139 & 140 North Ranges 26 W - set by M double preportion I located the corner to Townships 139 & 140 North Ranges 27 We and Townships 139 & 140 North Ranges 26 W - set by Indeed at Outing Minn, this James Adv of January 23 13 13 13 13 13 13 14 14 15 15 15 15 15 15 15 15 15 15 15 15 15							
and I further certify that to perpetuate the location of such corner I did at the exact location thereof place a perm ment marker consisting of an 1-2" iron pipe, 4-3" long, capped and stamped. I further certify that I established two bearing trees for reference or witness monuments consisting of an 8" Tamarack and a 12" lack Fine. which reference or witness monuments are located in the manner following: Tamarack 8" N 39 E 20.3Feet Jack Pine 12" N 19½ W 130.8 Feet. To locate this corner I started south from the accepted iron pipe corner to Sec. 25 & 36 T 140 N R 27 W and Sec. 30 & 31 T 140 N R 28 W - Set by County Surveyor Green in 1924 - on a line bearing S 6 W and ren four miles to the accepted iron pipe corner for Sec. 13 & 24 T 139 N R 27 W and Sec. 18 & 19 T 139 N R 26 W - Set be Deputy County Surveyor H. S. Todd - setting a temporary corner on the 1ce on Lake Corner for the corner to Townships 139 & 140 North Ranges 26 & 27 West. Then I started East from the accepted corner to Sec. 35 & 36 T 140 N R 27 W and Sec. 1 & 7 139 N R 28 W - Set by Deputy County Surveyor H. S. Todd and 1913 from original seridence and relocated by County Surveyor Green - on a line bearing N 84 E and ran the iron pipe 2 corner Sec. 31 T 140 N R 26 W and Sec. 6 T 159 N R 26 W - set by County Surveyor Green - setting a temporary corner to the four townships on the february Surveyor Green - setting a temporary corner to the four townships on the 18 M County Surveyor Green - setting a temporary corner to Sec. 36 T 140 N R 26 W - set by M 10 N R 26 W - set	I found the one-quart	er Co	orner to Sec.	31 T140N	R26W		·····
I further certify that I established two bearing trees for reference or witness monuments consisting of an 8" Tamarack and a 12" Jack Pine. which reference or witness monuments are located in the manner following: Tamarack 8" N 39 E 20.3Feet Jack Pine 12" N 19½ W 130.8 Feet. Te locate this corner I started south from the accepted from pipe corner to Sec. 25 & 36 T 140 N R 27 W and Sec. 30 & 31 T 140 N R 28 W - Set by County Surveyor Green in 1994 - on a line bearing S 6 W and ren four miles to the accepted iron pipe corner for Sec. 15 & 24 T 139 N R 27 W and Sec. 18 & 19 T 139 N R 26 W - Set located the corner for the certer to Townships 139 & 140 North Ranges 26 & 27 West. Then I started East from the accepted corner to Sec. 35 & 36 T 140 N R 27 W and Sec. 1 & W 139 N R 28 W - Set by Deputy County Surveyor H. S. Todd and 1913 from original evidence and relocated by County Surveyor Green - on a line bearing N 84 E and ran the iron pipe 1 corner Sec. 31 T 140 N R 26 W and Sec. 6 T 129 N R 26 W - set by County Surveyor Green - on a line bearing N 84 E and ran the iron pipe 1 corner Sec. 31 T 140 N R 26 W and Sec. 6 T 129 N R 26 W - set by County Surveyor Green - setting a temporary corner to the four townships on the iron pipe 1 corner sec. 31 T 140 N R 26 W and Sec. 6 T 129 N R 26 W - set by County Surveyor Green - setting a temporary corner to the four townships on the iron pipe 1 corner sec. 31 T 140 N R 26 W - set by County Surveyor Green - setting a temporary corner to Sec. 36 T 140 N R 26 W - set by County Surveyor Green - setting a temporary corner to Sec. 36 T 140 N R 26 W - set by County Surveyor Green - setting a temporary corner to Sec. 36 T 140 N R 26 W - set by County Surveyor M Sec. 31 T 140 N R 26 W - set by County Surveyor M Sec. 31 T 140 N R 26 W - set by County Surveyor M Sec. 31 T 140 N R 26 W - set by County Surveyor M Sec. 31 T 140 N R 26 W - set by County Surveyor M Sec. 31 T 140 N R 26 W - set by County Surveyor M Sec. 31 T 140 N R 26 W - set by County Surveyor M Sec. 31 T 140 N R 26 W -							
I further certify that I established two bearing trees for reference or witness monuments consisting of an 8" Tamarack and a 12" Jack Pine. which reference or witness monuments are located in the manner following: Tamarack 8" N 59 E 20.3Feet Jack Pine 12" N 19½ W 130.8 Feet. To locate this corner I started south from the accepted from pipe corner to Sec. 25 & 36 T 140 N R 27 W and Sec. 30 & 31 T 140 N R 25 W - Set by County Surveyor Green in 1924 - on a line bearing S 6 W and ran four miles to the accepted from pipe corner for Sec. 13 & 24 T 139 N R 27 W and Sec. 18 & 19 T 139 N R 26 W - Set l Deputy County Surveyor H. S. Todd - setting a temporary corner on the ice on Lake George for the corner to Townships 139 & 140 North Ranges 26 & 27 West. Then I started East from the accepted corner to Sec. 35 & 36 T 140 N R 27 W and Sec. 1 & T 139 N R 27 W - Set by Deputy County Surveyor H. S. Todd and 1913 from original evidence and relocated by County Surveyor Green - on a line bearing S 24 E and ran the irom pipe ½ corner Sec. 31 T 140 N R 26 W and Sec. 6 T 139 N R 26 W - set b County Surveyor Green - setting a temporary corner to the four townships on the ic County Surveyor Green - setting a temporary corner to the four townships on the ic Sec. 31 T 140 N R 26 W. On the above work I med a Curley Transit, a standard 100 foot start W and Dated at Outing Minn, this day of January 37 N 133 N	and I further certify that	to perpetuate the l	ocation of such	corner I did a	t the exact loca	tion thereof pla	ce a perma-
which reference or witness monuments consisting of an S. Tamarack and a 12" Jack Pine. which reference or witness monuments are located in the manner following: Tamarack S. N 39 E 20.3Feet Jack Pine 12" N 19½ W 130.8 Feet. To locate this corner I started south from the accepted from pipe corner to Sec. 25 & 36 T 140 N R 27 W and Sec. 30 & 31 T 140 N R 26 W - Set by County Surveyor Green in 1924 on a line bearing S 6 W and ren four miles to the accepted from pice corner fer Sec. 15 & 24 T 139 N R 27 W and Sec. 18 & 19 T 139 N R 26 W - Set located for the corner to Townships 139 & 140 North Ranges 26 & 27 West. Then I started East from the accepted corner to Sec. 35 & 36 T 140 N R 27 W and Sec. 1 & T 139 N R 28 W - Set by Deputy County Surveyor R. S. Todd and 1913 from original evidence and relocated by County Surveyor Green - on a line bearing M 24 R and ran the iron pipe 1 corner Sec. 31 T 140 N R 26 W and Sec. 6 T 139 N R 26 W - set by County Surveyor Creen - on a line bearing M 24 R and ran the iron pipe 2 corner Sec. 31 T 140 N R 26 W and Sec. 6 T 139 N R 26 W - set by County Surveyor Creen - on a line bearing M 24 R and ran the iron pipe 2 corner Sec. 31 T 140 N R 26 W and Sec. 6 T 139 N R 26 W - set by County Surveyor Creen - on a line bearing M 24 R and ran the iron pipe 2 corner Sec. 31 T 140 N R 26 W and Sec. 6 T 139 N R 26 W - set by County Surveyor Creen - on a line bearing M 24 R and ran the iron pipe 3 corner to Townships 139 & 140 North Ranges 27 We and Townships 139 & 140 North Ranges 26 West. Then by single proportion I located the corner to Townships 139 & 140 North Range 27 We and Townships 139 & 140 North Ranges 26 West. On the above work I mad a Curley Transit, a standard 100 foet start 18 M 2 M 2 M 2 M 2 M 2 M 2 M 2 M 2 M 2 M	nent marker consisting of	an 1-1" iron	pipe, 4-1'	long, capr	ed and star	aped.	
which reference or witness monuments consisting of an S. Tamarack and a 12" Jack Pine. which reference or witness monuments are located in the manner following: Tamarack S. N 39 E 20.3Feet Jack Pine 12" N 19½ W 130.8 Feet. To locate this corner I started south from the accepted from pipe corner to Sec. 25 & 36 T 140 N R 27 W and Sec. 30 & 31 T 140 N R 26 W - Set by County Surveyor Green in 1924 on a line bearing S 6 W and ren four miles to the accepted from pice corner fer Sec. 15 & 24 T 139 N R 27 W and Sec. 18 & 19 T 139 N R 26 W - Set located for the corner to Townships 139 & 140 North Ranges 26 & 27 West. Then I started East from the accepted corner to Sec. 35 & 36 T 140 N R 27 W and Sec. 1 & T 139 N R 28 W - Set by Deputy County Surveyor R. S. Todd and 1913 from original evidence and relocated by County Surveyor Green - on a line bearing M 24 R and ran the iron pipe 1 corner Sec. 31 T 140 N R 26 W and Sec. 6 T 139 N R 26 W - set by County Surveyor Creen - on a line bearing M 24 R and ran the iron pipe 2 corner Sec. 31 T 140 N R 26 W and Sec. 6 T 139 N R 26 W - set by County Surveyor Creen - on a line bearing M 24 R and ran the iron pipe 2 corner Sec. 31 T 140 N R 26 W and Sec. 6 T 139 N R 26 W - set by County Surveyor Creen - on a line bearing M 24 R and ran the iron pipe 2 corner Sec. 31 T 140 N R 26 W and Sec. 6 T 139 N R 26 W - set by County Surveyor Creen - on a line bearing M 24 R and ran the iron pipe 3 corner to Townships 139 & 140 North Ranges 27 We and Townships 139 & 140 North Ranges 26 West. Then by single proportion I located the corner to Townships 139 & 140 North Range 27 We and Townships 139 & 140 North Ranges 26 West. On the above work I mad a Curley Transit, a standard 100 foet start 18 M 2 M 2 M 2 M 2 M 2 M 2 M 2 M 2 M 2 M	I further certify tha	t I established two	bearing to	rees for			
Jack Pine 12" N 19½ W 150.8 Feet. Te locate this corner I started south from the accepted iron pipe corner to Sec. 25 & 36 T 140 N R 27 W and Sec. 30 & 31 T 140 N R 26 W - Set by County Surveyor Green in 1924 - on a line bearing S 6 W and ran four miles to the accepted iron pipe corner for Sec. 13 & 24 T 159 N R 27 W and Sec. 18 & 19 T 139 N R 26 W - Set located to Sec. 18 & 19 T 139 N R 26 W - Set located to Townships 139 & 140 North Ranges 26 & 27 West. Then I started East from the accepted corner to Sec. 35 & 36 T 140 N R 27 W and Sec. 1 & T 139 N R 28 W - Set by Deputy County Surveyor H. S. Todd and 1913 from original evidence and relocated by County Surveyor Green - on a line bearing M 84 R and ran the iron pipe ½ corner Sec. 31 T 140 N R 26 W and Sec. 6 T 139 N R 26 W - set by County Surveyor Green - setting a temporary corner to the four townships on the to By double proportion I located the corner to Townships 139 & 140 North Ranges 27 West. Then by single proportion I located the 1 corner to Sec 36 T 140 N R 27 W and Sec. 31 T 140 N R 26 W. On the above work I med a Curley Transit, a standard 100 foot steel 140 N R 27 W and Sec. 31 T 140 N R 26 W. Dated at Cuting Minn., this day of January 313 113 113 113 113 113 113 113 113 11							
Jack Pine 12" N 19½ W 130.8 Feet. To locate this corner I started south from the accepted iron pipe corner to Sec. 25 & 36 T 140 N R 27 W and Sec. 30 & 31 T 140 N R 26 W - Set by County Surveyor Green in 1924 - on a line bearing S 6 % and ran four miles to the accepted iron pic corner for Sec. 13 & 24 T 139 N R 27 W and Sec. 18 & 19 T 139 N R 26 W - Set Deputy County Surveyor H. S. Todd - setting a temporary corner on the ice on Lake George for the cerner to Townships 139 & 140 North Renges 26 & 27 West. Then I started East from the accepted corner to Sec. 35 & 36 T 140 N R 27 W and Sec. 1 & T 139 N R 23 W - Set by Deputy County Surveyor Green - on a line bearing N 84 E and ran the iron pipe ½ corner Sec. 31 T 140 N R 26 W and Sec. 6 T 139 N R 26 W - set by County Surveyor Green - setting a temporary corner to the four townships on the ice By double proportion I located the corner to Townships 139 & 140 North Ranges 26 West. Then by single proportion I located the ½ corner to Sec 36 T 140 N R 27 Wend Sec. 31 T 140 N R 26 W. On the above work I used a Curley Transit, a standard 100 foet steel the Sec. 31 T 140 N R 26 W. On the above work I used a Curley Transit, a standard 100 foet steel the Sec. 31 T 140 N R 26 W. On the above work I used a Curley Transit, a standard 100 foet steel the Sec. 31 T 140 N R 26 W. On the above work I used a Curley Transit, a standard 100 foet steel the Sec. 31 T 140 N R 26 W. On the above work I used a Curley Transit, a standard 100 foet steel the Sec. 31 T 140 N R 26 W. Office of Register of Deeds Sec. 1 T 140 N R 26 W and Sec. 6 T 130 N R 26 W. Office of Register of Deeds Sec. 1 T 140 N R 26 W and Sec. 1 T 140 N R 26 W and Sec. 1 T 140 N R 26 W and Sec. 1 T 140 N R 26 W and Sec. 1 T 140 N R 26 W and Sec. 1 T 140 N R 26 W and Sec. 1 T 140 N R 26 W and Sec. 1 T 140 N R 26 W and Sec. 1 T 140 N R 26 W and Sec. 1 T 140 N R 26 W and Sec. 1 T 140 N R 26 W and Sec. 1 T 140 N R 26 W and Sec. 1 T 140 N R 26 W and Sec. 1 T 140 N R 26 W and Sec. 1 T 140 N R 26 W and Sec. 1 T 140 N R	which reference or witness	s monuments are lo	cated in the ma	nner following	•		
Dated at Outing Minn., this day of January 3343131343 Office of Register of Deeds ss. County of I hereby certify that the within instrument was filed in this office for record on the day of A. D. 19 , at o'clock M.	Tamarack 8"	N 39 E	20.3Fee	<u>t</u>			
To locate this corner I started south from the accepted from pipe corner to Sec. 25 & 36 T 140 N R 27 W and Sec. 30 & 31 T 140 N R 26 W - Set by County Surveyor Green in 1924 - on a line bearing S 6 W and ran four miles to the accepted from piccorner fer Sec. 13 & 24 T 139 N R 27 W and Sec. 18 & 19 T 139 N R 26 W - Set leaving of the corner for Sec. 13 & 24 T 139 N R 27 W and Sec. 18 & 19 T 139 N R 26 W - Set leaving of the corner to Townships 139 & 140 North Ranges 26 & 27 West. Then I started East from the accepted corner to Sec. 35 & 36 T 140 N R 27 W and Sec. 1 & T 139 N R 25 W - Set by Deputy County Surveyor H. S. Todd and 1913 from original evidence and relocated by County Surveyor Green - on a line bearing M 84 E and ran the irom pipe 1 corner Sec. 31 T 140 N R 26 W and Sec. 6 T 139 N R 26 W - set by double proportion I located the corner to Townships 139 & 140 North Ranges 26 West. Then by single proportion I located the 1 corner to Sec 36 T 140 N R 27 W and Sec. 31 T 140 N R 26 W. On the above work I med a Curley Transit, a standard 100 foot step 1 M 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Jack Pine 12"	' N 19½ W	130.8 Fe	et.			
Office of Register of Deeds Ss. County of I hereby certify that the within instrument was filed in this office for record on the day of	corner for Sec. 13 Deputy County Surve George for the corn started East from t T 139 N R 29 W - S evidence and reloca the iron pipe \$\frac{1}{2}\$ cor County Surveyor Gre By double proportic and Townships 139 8 Then by single Sec. 31 T 140 N I	& 24 T 139 N eyer H. S. Todd eer to Township the accepted co set by Deputy (ated by County rner Sec. 31 T sen - setting a on I located the k 140 North Rai proportion I R 26 W. ork I wand a G	R 27 W and 1 - setting post 139 & 14 priner to Secounty Surveyor G 140 N R 2 a temporary the corner tonges 26 Westlecated the curley Trans	a temporar o North Re c. 35 & 36 eyor H. S. reen - on a 6 W and Sec corner to o Townships t. d corner	T 140 N R Todd and 1 Line bear the four to 139 & 140 to Sec 36 T	N R 26 W a the ice or 27 West. 27 W and Se 913 from ori ing N 84 E a N R 26 W commships on North Range	Lake Then I oc. 1 & 2 iginal and ran t set by the ice. 27 West
Office of Register of Deeds Ss. County of I hereby certify that the within instrument was filed in this office for record on the day of	_		_	day of	January	EK E	ialon 3
	County of	t the within instru					19193
Register of Deeds	day of	А	. <i></i> , a	υΟ (AUCA		
11081.10 01 2001						Register	of Deeds.

A000560849
OFFICE OF COUNTY RECORDER
CASS COUNTY MINNESOTA
CERTIFIED, FILED, AND/OR
RECORDED ON
06/07/2010 2:14:09 PM
AS DOC #: A000560849
PAGES: 2 REC FEES: 0.00
KATHRYN M. NORBY
COUNTY RECORDER