

# CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

East Quarter corner of Section 01, Township 145 N., Range 30 W., 5th P.M.  
 State of Minnesota, County of Cass

At the corner location shown on the sketch:

On 03-24-2011 found a 1" iron pipe with a 2.5" diameter GLO brass cap,  
12" above surface grade.

left monument as found       lowered monument       removed monument (explain)

On \_\_\_\_\_ placed \_\_\_\_\_



## SKETCH OF REFERENCE TIES (NOT TO SCALE)




Note:  
No other trees suitable for ties.

SECTION 1,  
T145N, R30W

SECTION 6,  
T145N, R29W

Existing Tie:  
Found a spike with a tag  
stamped "N62°E 7.42" in the  
westerly face of a 6" Balsam.



Existing Tie:  
Found a spike with a tag stamped  
"N34°W 9.72" in the  
southwesterly face of a 6" Balsam.

NOTE: All bearings are true.

Statement of evidence relative to this corner location is on the back of this page.

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly Licensed land Surveyor under the laws of the State of Minnesota. I further certify that this United States public land survey monument record is correct and complete to the best of my knowledge and belief.

Terry L. Freeman, Land Surveyor

Date 2/28/12 MN License No. 21367

**A000578278**  
**OFFICE OF COUNTY RECORDER**  
**CASS COUNTY MINNESOTA**  
**CERTIFIED, FILED, AND/OR**  
**RECORDED ON**  
**03/01/2012 2:29:14 PM**  
**AS DOC #: A000578278**  
**PAGES: 2 REC FEES: 0.00**  
**KATHRYN M. NORBY**  
**COUNTY RECORDER**

Index No. C.0 - 25.0

**STATEMENT ON EVIDENCE**

**East Quarter Corner of Section 01, Township 145 North, Range 30 West of the 5th Principal Meridian.**

**In 1873**, P.H. Conger, U.S. Deputy Surveyor, set the original wood post and bearing trees as follows: a 4" Spruce, S75°W 7 links; a 3" Spruce, N29°E 8 links.

**1900 and 1903**, U.S. Army Corp of Engineers maps for the Leech Lake and Lake Winnibigoshish Reservoirs show corner found by surveyors T. Milton Fowble, Horace Dunaway, and W.C. Lemen. A copy of the map is on file in the Cass County Survey Department.

**In 1933**, W. W. Bandy, United States Cadastral Engineer, found remains of the 2 original BTs: a 12" Spruce stump, S75°W 7 links; a Spruce stump (rotten), N29°E 8 links. He set a 1" x 36" iron post with a brass cap, and established new BTs as follows: a 4" Tamarack, N62 1/4°E 28 links; a 8" Spruce, N39 1/2°W 18 links. Notes on file in the Cass County Surveyors office.

**On August 28, 1962**, R.H. McDonald, a U.S. Forest Surveyor, found the 1" iron pipe with brass cap in place. They found GLO BTs as recorded by Bandy in 1933 as follows: now a 5" Tamarack, N62 1/2°E 18.48'; a Spruce stump (rotten), N39 1/2°W 11.88'. He recorded a new bearing tree: a 4" Spruce, S75°E 16.3'. He also set a 72" steel sign post 3.1" west of the corner. On December 10, 1962 Peter J. Meyer filed an Affidavit as to Location of Government Corner using this information. Notes on file in the U.S.F.S. Cass Lake office in T145N R30W Book 1, Pg. 19.

**On October 28, 2008**, Rob Main, U.S.F.S. personnel found iron in place, found a 4" cedar post west 3.1 feet, and set spikes in two new BT's: a 6" Balsam, S62°W 7.42 feet; and a 6" Balsam, S34°E 9.72 feet. Notes on file in U.S.F.S. Cass Lake office in T145N R30W Book 1, page 19.

**On March 24, 2011**, a Northern Engineering & Consulting survey crew found a 1" iron pipe with a 2.5" diameter GLO brass cap, 12" above surface grade. Two existing ties, marked in 2008 by U.S.F.S. personnel, were found as shown on the front of this certificate. The corner is accepted as a perpetuation of the original corner.

**Minnesota State Plane (Central Zone)**

Northing 1205029.134  
Easting 2583550.388

**County Coordinates (Cass County North)**

Northing 319272.547  
Easting 450629.501