

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

Northeast corner of Section 03, Township 145 N., Range 29 W., 5th P.M.
 State of Minnesota, County of Cass

At the corner location shown on the sketch:

On 04-11-2011 found a 6" concrete monument with a brass cap,
 30" below the surface grade in a bog.

left monument as found lowered monument removed monument (explain)

On 04-11-2011 placed 1/2" x 2' long rebar w/ stamped brass cap
 over concrete monument

8 0 3 2 9 1 5
 Tx:4023348



SKETCH OF REFERENCE TIES (NOT TO SCALE)


SECTION 34,
T146N, R29W

SECTION 35,
T146N, R29W

MISSISSIPPI RIVER

LAKE WINNIE

Set New Tie:
Set nail in southeasterly
face of a 14" Oak.



Set New Tie:
Set nail in southwesterly
face of a 26" Norway Pine.

SECTION 3,
T145N, R29W

Set New Tie:
Set nail in westerly
root of a 40" White
Pine.

Existing 1934 Tie:
Set nail in
southeasterly face
of a 16" Jack Pine
stump.

SECTION 2,
T145N, R29W

NOTE: All bearings are true.

Statement of evidence relative to this corner location is on the back of this page.

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly Licensed land Surveyor under the laws of the State of Minnesota. I further certify that this United States public land survey monument record is correct and complete to the best of my knowledge and belief.

Terry L. Freeman, Land Surveyor

Date

2/28/12

MN License No. 21367

A000578280
OFFICE OF COUNTY RECORDER
CASS COUNTY MINNESOTA
CERTIFIED, FILED, AND/OR
RECORDED ON
03/01/2012 2:29:16 PM
AS DOC #: A000578280
PAGES: 2 REC FEES: 0.00
KATHRYN M. NORBY
COUNTY RECORDER

Index No. A.0 - 17.0

STATEMENT ON EVIDENCE

Northeast Corner of Section 03, Township 145 North, Range 29 West of the 5th Principal Meridian.

In 1873, P.H. Conger, U.S. Deputy Surveyor, set a wood post in place to mark the location of this corner and established bearing trees as follows: a 12" Cedar, N29°E 9 links; a 4" Fir, N53°W 12 links; a 12" Cedar, S58 1/2°W 4 links; a 8" Cedar, S32°E 7 links.

1902 - 1903, U.S. Army Corp of Engineers map for the Lake Winnibigoshish Reservoir shows corner found by T. Milton Fowble and W.C. Lemen.

In 1934, H. Craig and A. Berger, United States Cadastral Engineers, made a dependent resurvey of the South Boundary of T146N, R29W, and found no remains of the original monument or BTs. He set a 6" dia. x 24" concrete monument with a 3 1/2" dia. brass tablet, and established three new bearing trees as follows: a 13" Jack Pine, S44-3/4°E, 116 links; a 7" Norway Pine, S40°W, 50 links; a 14" charred pine stump, N16-3/4°W, 42 links. (Running notes on file in Cass County Survey Department)

On October 25, 1974, C. Krause, a U.S. Forest Surveyor, found the concrete monument in place, under bog 30", in front of a green cabin, 30' out on bog grass. He also found the bearing trees as recorded by Craig and Berger in 1934 as follows: now a 17" Jack Pine, S45°E, 76.6'; now a 12" Norway Pine (stub), S40°W, 33'; a 14" charred pine stump, N16-3/4°W, 42 links, 27.72' which falls in bog, very soft bottom. Notes on file in U.S.F.S. Cass Lake office in T146N R29W Book 1, Pg. 13.

On April 11, 2011, a Northern Engineering & Consulting survey crew found the concrete monument with "G.L.O." cap, down 30" in bog. They set a 2' long 1/2" rebar with a 3.5" diameter brass cap, flush with the surface grade and found a 1934 BT as follows: a 16" Jack Pine (stump), up 12', with a blaze and scribe, matching the 1934 tie. Three new ties were set as shown on the front of this certificate.

Minnesota State Plane (Central Zone)

Northing 1208288.430
Easting 2604789.907

County Coordinates (Cass County North)

Northing 322522.283
Easting 471869.963

