

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

Closing Northeast corner of Section 01, Township 144 N., Range 31 W., 5th P.M.

State of Minnesota, County of Cass

At the corner location shown on the sketch:

On 05-04-2011 found a 3" iron pipe with a 3.5" GLO brass cap, 12" above surface grade,
mounded dirt around monument.

left monument as found lowered monument removed monument (explain)

On _____ placed _____



SKETCH OF REFERENCE TIES (NOT TO SCALE)



SECTION 31,
T145N, R30W


Set New Tie:
Set nail in southwesterly
face of a 10" twin Maple.




Set New Tie:
Set nail in southeasterly
face of an 11" Oak.



Existing (2009 USFS) Tie:
Found a spike with a tag
stamped "N 72° E 9.32" in
the northerly face of a 17"
Oak, with a blaze.



1930 GLO Tie:
Set nail in tree with an existing
tag stamped "N 15° W 19.80" in
the westerly face of an 18" Oak.



SECTION 1,
T144N, R31W

SECTION 6,
T144N, R30W

NOTE: All bearings are true.

Statement of evidence relative to this corner location is on the back of this page.

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly Licensed land Surveyor under the laws of the State of Minnesota. I further certify that this United States public land survey monument record is correct and complete to the best of my knowledge and belief.

Terry L. Freeman, Land Surveyor

Date 12/9/11

MN License No. 21367

A000578291
OFFICE OF COUNTY RECORDER
CASS COUNTY MINNESOTA
CERTIFIED, FILED, AND/OR
RECORDED ON
03/01/2012 2:29:27 PM
AS DOC #: A000578291
PAGES: 2 REC FEES: 0.00
KATHRYN M. NORBY
COUNTY RECORDER

Index No. A.0 - 25.0

STATEMENT ON EVIDENCE

Closing North East Corner of Section 1, Township 144 North, Range 31 West of the 5th Principal Meridian.

In 1875, Benjamin C. Baldwin, U.S. Deputy Surveyor, set a wood post in place to mark the location of this corner and established bearing trees as follows: a 6" Red Oak, S60°E 21 links; a 6" Burr Oak, S46°W 37 links.

In 1930, H. Craig, United States Surveyor, made a dependent resurvey part of the south boundary of Township 145 North. He set a 3" x 36" iron pipe with brass cap by proportionate measurement and recorded two new BTs: a 4" Burr Oak, S15°E 30 links; a 8" Poplar, S64°W 14 links. Running notes on file in the Cass County Survey Department.

2009, Rob Main, U.S.F.S. personnel, placed tag on 1930 southeast BT and marked a new BT, 17" Oak, S72°W, 9.32 feet. Information taken from BT tags on trees - no information on corner visit in U.S.F.S. field books.

On May 4, 2011, a Northern Engineering & Consulting survey crew found a 3" iron pipe, with a 3 1/2" GLO brass cap, 12" above surface grade (mounded dirt around base). Two existing ties were found and two new ties were set as shown on the front page of this certificate. We accept the position monumented in 1930 at the lost position.

Minnesota State Plane (Central Zone)

Northing 1175506.727
Easting 2553759.994

County Coordinates (Cass County North)

Northing 289764.329
Easting 420825.827

