



STATEMENT OF EVIDENCE**East Quarter Corner of Section 19, Township 135 North, Range 32 West, 5<sup>th</sup> P.M.**

The Department of Natural Resources, Division of Lands and Minerals, contacted the following offices for information regarding this corner:

MN History Center  
 Wadena County Highway Dept.  
 Cass County Surveyor  
 Wadena County Recorder  
 Nyberg Surveying  
 Roy Smith, Land Surveyor

1866 The US General Land Office field notes, on file in the History Center, show this corner to be marked with a post and the following bearing trees:

Tamarac	5"	N 51° W	6 links
Tamarac	5"	N 27° E	23 links

1920 County Book "C" page 368, on file at the Cass County Surveyor's office, indicates that E.B. Horst, Cass County Engineer, and Lincoln Mackey, assistant, found old BT's and set an iron monument and took new ties:

Jack Pine	6"	S 82°42' W	94.1'
Jack Pine	8"	N 65°03' W	135.0'

A distance of 2620.9' was measured to the northeast corner of section 19.

2012 In February, the DNR survey crew searched for evidence of the corner found a 1 ¼" x 48" inside diameter iron pipe in a swamp. No other evidence of the corner was recovered. The iron pipe was accepted as the pipe set by Horst and a perpetuation of the corner location.

Northeast Corner of Section 19 bears N01°57'53"W 2620.83'

For information on our survey in this area, please contact the MN DNR, Division of Lands and Minerals, Survey Section, 1601 Minnesota Drive, Brainerd, MN 56401