



A000583887

**OFFICE OF THE COUNTY RECORDER
CASS COUNTY, MINNESOTA
CERTIFIED, FILED, AND/OR
RECORDED ON**

9/7/2012 1:16:21 PM

AS DOC #: A000583887

PAGES: 3

REC FEES: 0.00

**KATHRYN M. NORBY
CASS COUNTY RECORDER**

BY KF Dep

AFFIDAVIT BY THE CASS COUNTY SURVEYOR IN REGARD TO A CERTIFICATE OF LOCATION OF GOVERNMENT CORNER


STATE OF MINNESOTA }
 }ss
COUNTY OF CASS }

Robert Kovanen, being first duly sworn, deposes and states as follows:

That Affiant is the County Surveyor in and for the County of Cass, in the State of Minnesota;

That in such capacity Affiant has knowledge of the books and records kept in the Office of the County Surveyor in and for the County of Cass, State of Minnesota;

That the attached CERTIFICATE OF LOCATION OF GOVERNMENT CORNER has been found in the Surveyor's records and after checking with the Cass County Recorder, it was determined that the document was never assigned a document number and was never officially recorded in the real estate records or tracted in the tract indexes within said Cass County Recorder's Office;





-2-

That in order to make the attached CERTIFICATE OF LOCATION OF GOVERNMENT CORNER a matter of public record and locatable by legal description, Affiant does herewith attach said document to this affidavit and requests the Cass County Recorder to record same at her earliest opportunity.

FURTHER, Affiant sayeth not.

Robert Kovanen, Cass County Surveyor

Subscribed and sworn to before me
this 30 day of August, 2012.

Notary Public



This instrument was drafted by:

Robert Kovanen
Cass County Surveyor
P.O. Box 579
Walker, MN 56484

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

Corner to Sec. 17 - 16 - 20 - 21 T. 137 N. R. 29 W.

State of Minnesota, }
 COUNTY OF CASS } ss.

I hereby certify that on the 16th day of May 1922

I found the section corners of Sec. 16, 17, 20, & 21, T. 137 N., R. 29 W. which was evidenced by 2" Iron Pipe set in concrete by John Guro, Co. Surveyor location of which was reserved during construction of Pine River-Jenkins State Road, and I further certify that to perpetuate the location of such corner I did at the exact location thereof place a permanent marker consisting of 2" hollow iron pipe 3 1/2 feet long

I further certify that I established Four reference or witness monuments consisting of 2" hollow iron pipes 3 1/2 feet long which reference or witness monuments are located in the manner following:

- 2" hollow iron pipe SW 46.7 feet
- 2" " " " SE 46.7 "
- 2" " " " NW 46.7 "
- 2" " " " NE 46.7 "

All pipes 4 inches above surface of the ground

Pine River
 Dated at ~~Walker~~ this 17th day of May 1922

C. J. Bark
 C. J. Bark
 Asst. ~~County Surveyor~~ Highway Engineer

OFFICE OF REGISTER OF DEEDS, }
 COUNTY OF CASS }

I hereby certify that the within instrument was filed in this office for record on the 17th day of Nov. A. D. 1922 at 9 o'clock P. M., and was duly Recorded in Book 1 of *Gov. Cas* on page

Adrian Husted
 Register of Deeds.

By _____ Deputy.