

A000584130

OFFICE OF THE COUNTY RECORDER CASS COUNTY, MINNESOTA CERTIFIED, FILED, AND/OR RECORDED ON

9/11/2012 1:01:23 PM AS DOC #: A000584130 PAGES: 4

REC FEES: 0.00

KATHRYN M. NORBY CASS COUNTY RECORDER

BY<u>KF</u>Dep

## AFFIDAVIT BY THE CASS COUNTY SURVEYOR IN REGARD TO AN AFFIDAVIT AS TO LOCATION OF A GOVERNMENT CORNER

STATE OF MINNESOTA }

ss

COUNTY OF CASS }

Robert Kovanen, being first duly sworn, deposes and states as follows:


That Affiant is the County Surveyor in and for the County of Cass, in the State of Minnesota;

That in such capacity Affiant has knowledge of the books and records kept in the Office of the County Surveyor in and for the County of Cass, State of Minnesota;

That the attached AFFIDAVIT AS TO LOCATION OF GOVERNMENT CORNER has been found in the Surveyor's records and after checking with the Cass County Recorder, it was determined that the document was never assigned a document number and was never officially recorded in the real estate records or tracted in the tract indexes within said Cass County Recorder's Office;



description, Affiant does herewith attach said document to this affidavit and requests the Cass County Recorder to record same at her earliest opportunity.



FURTHER, Affiant sayeth not.

Robert Kovanen, Cass County Surveyor

Subscribed and sworn to before me this 67 day of 5897, 2012.

ROBERT H. YOCHUM
Notary Papir.
Steffe of Minimesolo.
My Comm. Exp. 1.31.201.5

Notary Public

This instrument was drafted by:

Robert Kovanen Cass County Surveyor P.O. Box 579 Walker, MN 56484

## AFFIDAVIT AS TO LOCATION OF GOVERNMENT CORNER

Center west 1/15						
Corner to Sec	21	T.	142N	R	30N	 

## State of Minnesota, County of Cass

and distance).

Peter J. Meyer	, being first duly sworn, deposes ar	ıd says:
That I reside at Cass Lake , Minn.		
laws of the State of Minnesota, having Surveyor's Regist	tration Certificate No3628	
I further depose and say that on the 21st	day of January	, 1 <i>9</i> 4 ,
found the Center West 1/16 corner of Section	on 21	
which was evidenced by the remains of the GLO s		
l inch diameter iron post with a brass cap st	camped: $C = \frac{W \frac{1}{16}}{S \frac{21}{21}} C$	
Red Pine 5 inch S7°E 41 links or 27.06 feet	0 21	
14 inch red pine at record bearing and distant		
Red Pine 5 inch N3510W 60 links or 39.6 feet		ecord bearing

and that to perpetuate the location of such corner I did, at the exact location thereof, place a permanent marker consisting of No new monument set as the GLO brass cap is in good condition.

from which reference or witness monuments are located in the manner following:

Red Pine 14 inch S7°E 27.06 feet rescribed "BT" Red Pine 11 inch N34°W 39.6 feet rescribed "BT"

Steel sign post 72 inches long, set 24 inches in ground with F.S. Standard signs 54-2 and 54-4 attached due North 4.0 feet.

All reference bearings are true bearings.

Cut Meyor	
(Surveyor's Signature)	
In the Presence of: //	
Beulah Sendricks	
Jane Cino Relson	,
Subscribed and sworn to before me at	
Walker, Minnesota:	
this 10th day of June	, 19 64
Quilekon Gendricks	•
Nebary Public -	

## OFFICE OF REGISTER OF DEEDS

County of Cass	
I hereby certify that the filed in this office for record	
day of June	A.D., 1964
at 9 o'clock A.M.	
Leonard P. Peters	on f.Deeds v.Aucks Denuty
By Beulah Ve	ndick Deputy

Page 4 of 4 A000584130

