

A000584235

OFFICE OF THE COUNTY RECORDER CASS COUNTY, MINNESOTA CERTIFIED, FILED, AND/OR RECORDED ON

9/12/2012 11:04:28 AM
AS DOC #: A000584235
PAGES: 4
REC FEES: 0.00
KATHRYN M. NORBY
CASS COUNTY RECORDER

BY SR Dep

AFFIDAVIT BY THE CASS COUNTY SURVEYOR IN REGARD TO AN AFFIDAVIT AS TO LOCATION OF A GOVERNMENT CORNER

STATE OF MINNESOTA }

ss

COUNTY OF CASS }

Robert Kovanen, being first duly sworn, deposes and states as follows:

That Affiant is the County Surveyor in and for the County of Cass, in the State of Minnesota;

That in such capacity Affiant has knowledge of the books and records kept in the Office of the County Surveyor in and for the County of Cass, State of Mirnesota;

That the attached AFFIDAVIT AS TO LOCATION OF GOVERNMENT CORNER has been found in the Surveyor's records and after checking with the Cass County Recorder, it was determined that the document was never assigned a document number and was never officially recorded in the real estate records or tracted in the tract indexes within said Cass County Recorder's Office;



-2-

ge 2 of 4 A000584235

That in order to make the attached AFFIDAVIT AS TO LOCATION OF GOVERNMENT CORNER a matter of public record and locatable by legal description, Affiant does herewith attach said document to this affidavit and requests the Cass County Recorder to record same at her earliest opportunity.

FURTHER, Affiant sayeth not.

Robert Kovanen, Cass County Surveyor

Subscribed and sworn to before me

this & day of Supt, 20/2.

Linda Columbia

Notary Public

UNDA C. HUSBY
Notary Public
State of Minnesota
My Comm. Exp. 1-31-2015

This instrument was drafted by:

Robert Kovanen Cass County Surveyor P.O. Box 579 Walker, MN 56484

AFFIDAVIT AS TO LOCATION OF GOVERNMENT CORNER

Clm 9 inch N56°E 37.7 feet Cedar 4 inch S55°E 22.3 feet J. Pine 11 inch S46°W 25.2 feet		T. 141N	R. 27W	
William H. Okerman , being first duly sworn, deposes and says: That I reside at Bemidji , Minnesota , and am registered as a Land Surveyor under sws of the State of Minnesota, having Surveyor's Registration Certificate No. 6807. I further depose and say that on the 5th day of September , 19 found the Meander corner of Sections 7 - 18 hich was evidenced by remains of the G.L.O. resurvey of 1919 consisting of 1 inch diamete ron post 3 feet long with brass cap marked I. Pine 15 inch N45°W 15.18 feet - now 22 inch at record bearing all stance Poplar 15 inch S82°W 45°W 64.02 feet - not found and that to perpetuate the location of such corner I did, at the exact location thereof, place a permanent manuscristing of no new monument set as G.L.O. monument is in good condition. The property of the same of the content of the manner following: The property of the same of the content of the manner following: The property of the same of the content of the manner following: The property of the same of the manner following: The property of the same of the same of the manner following: The property of the same of the manner following: The property of the same of the manner following: The property of the same of the manner following: The property of the same of the manner following: The property of the same of the same of the manner following: The property of the same of the same of the manner following: The property of the same of the same of the manner following: The property of the same of the same of the manner following: The property of the same	State of Minnesota,			
That I reside at Bemidji , Minnesota , and am registered as a Land Surveyor under aws of the State of Minnesota, having Surveyor's Registration Certificate No. 6807 I further depose and say that on the 5th day of September , 19 found the Meander corner of Sections 7 - 18 hich was evidenced by remains of the G.L.O. resurvey of 1919 consisting of 1 inch diameter ron post 3 feet long with brass cap marked T1LilN S7 S7 S18 nd distance R27W 1919 Toplar 15 inch S82°W 45°W 64.02 feet - not found 1919 That I reside at Bemidji , Minnesota , and am registered as a Land Surveyor under was evidenced by September , 19 found the day of September , 19 found the manner following in the service of the S82°W 15.18 feet - 10 found 1919 That I reside at Mayor September	<i>``88.</i>			
That I reside at Bemidji , Minnesota , and am registered as a Land Surveyor under aws of the State of Minnesota, having Surveyor's Registration Certificate No. 6807 I further depose and say that on the 5th day of September , 19 found the Meander corner of Sections 7 - 18 hich was evidenced by remains of the G.L.O. resurvey of 1919 consisting of 1 inch diameter ron post 3 feet long with brass cap marked T1LilN S7 I. Pine 15 inch N45°W 15.18 feet - now 22 inch at record bearing and distance R27W Poplar 15 inch S82°W 45°W 64.02 feet - not found Indicate the location of such corner I did, at the exact location thereof, place a permanent many missisting of no new monument set as G.L.O. monument is in good condition. From which reference or witness monuments are located in the manner following: Class 9 inch N56°E 37.7 feet Class 9 inch N56°E 22.3 feet Class 1 inch S46°W 25.2 feet	William H. Okerman	, bei:	ng first duly sworn, depos	ses and says:
I further depose and say that on the 5th day of September ,19 found the Meander corner of Sections 7 - 18 hich was evidenced by remains of the G.L.O. resurvey of 1919 consisting of 1 inch diamete ron post 3 feet long with brass cap marked I. Pine 15 inch N45°W 15.18 feet - now 22 inch at record bearing and distance Poplar 15 inch S82°W 45 W 64.02 feet - not found Ind that to perpetuate the location of such corner I did, at the exact location thereof, place a permanent manusisting of no new monument set as G.L.O. monument is in good condition. From which reference or witness monuments are located in the manner following: Sim 9 inch N56°E 37.7 feet Sedar 4 inch S55°E 22.3 feet I. Pine 11 inch S46°W 25.2 feet				
I further depose and say that on the 5th day of September ,19 found the Meander corner of Sections 7 - 18 hich was evidenced by remains of the G.L.O. resurvey of 1919 consisting of 1 inch diameter on post 3 feet long with brass cap marked I. Pine 15 inch N45°W 15.18 feet - now 22 inch at record bearing and distance Poplar 15 inch S82°W 45°W 64.02 feet - not found Indicate the location of such corner I did, at the exact location thereof, place a permanent management of no new monument set as G.L.O. monument is in good condition. From which reference or witness monuments are located in the manner following: Sim 9 inch N56°E 37.7 feet Sedar 4 inch S55°E 22.3 feet 1. Pine 11 inch S46°W 25.2 feet				•
found the Meander corner of Sections 7 - 18 Thich was evidenced by remains of the G.L.O. resurvey of 1919 consisting of 1 inch diameter on post 3 feet long with brass cap marked Think S7 Think S7 Think S18 The L5 inch N45°W 15.18 feet - now 22 inch at record bearing and distance Toplar 15 inch S82°W 45°W 64.02 feet - not found The section of such corner I did, at the exact location thereof, place a permanent many manisting of no new monument set as G.L.O. monument is in good condition. The section of the section of such corner I did, at the manner following: The pinch N56°E 37.7 feet ledar 4 inch S55°E 22.3 feet The line S46°W 25.2 feet				
Thin post 3 feet long with brass cap marked I. Pine 15 inch N45°W 15.18 feet - now 22 inch at record bearing R27W Indicate Poplar 15 inch S82°W 45°W 64.02 feet - not found Indicate Poplar 15 inch S82°W 45°W 64.02 f				
I. Pine 15 inch N45°W 15.18 feet - now 22 inch at record bearing R27W 1919 Poplar 15 inch S82°W 45 W 64.02 feet - not found Ind that to perpetuate the location of such corner I did, at the exact location thereof, place a permanent man consisting of no new monument set as G.L.O. monument is in good condition. From which reference or witness monuments are located in the manner following: Clm 9 inch N56°E 37.7 feet Cedar 4 inch S55°E 22.3 feet J. Pine 11 inch S46°W 25.2 feet	hich was evidenced by remains or ron post 3 feet long with bra	f the G.L.O. resurvey ass cap marked	of 1919 consisting o	T 1.4.LN
oplar 15 inch S82°W 45°W 64.02 feet - not found and that to perpetuate the location of such corner I did, at the exact location thereof, place a permanent many posisting of no new monument set as G.L.O. monument is in good condition. From which reference or witness monuments are located in the manner following: Clm 9 inch N56°E 37.7 feet Cedar 4 inch S55°E 22.3 feet J. Pine 11 inch S46°W 25.2 feet		8 feet - now 22 inch a	at record bearing	S18 R27 W
rom which reference or witness monuments are located in the manner following: Clm 9 inch N56°E 37.7 feet Cedar 4 inch S55°E 22.3 feet 7. Pine 11 inch S46°W 25.2 feet	Coplar 15 inch S82°W 45°W	64.02 feet - not found	d	1/1/
From which reference or witness monuments are located in the manner following: Elm 9 inch N56°E 37.7 feet Cedar 4 inch S55°E 22.3 feet N. Pine 11 inch S46°W 25.2 feet				•
From which reference or witness monuments are located in the manner following: Elm 9 inch N56°E 37.7 feet Cedar 4 inch S55°E 22.3 feet W. Pine 11 inch S46°W 25.2 feet All reference bearings are true bearings.	instating of the mornal of the	o do delle de morramorro	20 21 5000	
Elm 9 inch N56°E 37.7 feet Cedar 4 inch S55°E 22.3 feet V. Pine 11 inch S46°W 25.2 feet				
Clm 9 inch N56°E 37.7 feet Cedar 4 inch S55°E 22.3 feet V. Pine 11 inch S46°W 25.2 feet				
Clm 9 inch N56°E 37.7 feet Cedar 4 inch S55°E 22.3 feet V. Pine 11 inch S46°W 25.2 feet			,	
Cedar 4 inch \$55°E 22.3 feet I. Pine 11 inch \$46°W 25.2 feet				
All reference bearings are true bearings.	rom which reference or witness mon	uments are located in the r	manner following:	
	Ilm 9 inch N56°E 37.7 feet Dedar 4 inch S55°E 22.3 fe	e t	manner following:	
	Im 9 inch N56°E 37.7 feet Sedar 4 inch S55°E 22.3 fe J. Pine 11 inch S46°W 25.2	et feet	manner following:	

(Surveyor's Signature)

In the Presence of:

September 19 September 19 Subscribed and sworn to before me at

Cass Lake, Minnesota

this 30 to day of April 19 70.

Notary Public

OFFICE OF REGISTER OF DEEDS

County of	Cass	
	certify that the w s office for record on	ithin instrument was the 19th
day of Fe	bruary	A.D., 1971
at9	o'clock AM.	
1321	lel Herre	bricks
.,,	Register of	Deeds

Page 3 of 4 A000584235

.....Deputy

age 4 of 4 A000584235

一点 人名英格兰 的复数 计记录 电电流转换

SECTION_____TOWNSHIP_____RANGE______P.M.

