





-2-


That in order to make the attached CERTIFICATE OF LOCATION OF GOVERNMENT CORNER a matter of public record and locatable by legal description, Affiant does herewith attach said document to this affidavit and requests the Cass County Recorder to record same at her earliest opportunity.

FURTHER, Affiant sayeth not.

Robert Kovanen, Cass County Surveyor

Subscribed and sworn to before me  
this 26<sup>th</sup> day of DEC, 2012

Notary Public



This instrument was drafted by:

Robert Kovanen  
Cass County Surveyor  
P.O. Box 579  
Walker, MN 56484

## AFFIDAVIT AS TO LOCATION OF GOVERNMENT CORNER

Corner to Sec. s 25 - 30 - 31 - 36 T. 141N R. 28 &amp; 29 W No. 492

State of Minnesota, }  
 County of Cass } ss.

William H. Okernan, being first duly sworn, deposes and says:

That I reside at Bemidji, Minnesota, and am registered as a Land Surveyor under the laws of the State of Minnesota, having Surveyor's Registration Certificate No. 6807.

I further depose and say that on the 16th day of November, 1964, I found the Section corner of Sections 25 - 30 - 31 - 36 which was evidenced by remains of a survey by Cass County Surveyor John Curo, Notes are on record in Cass County courthouse.

Norway Pine 22 inch N50° W 137 feet (Now a 23 inch N Pine N50° W 137.0 feet)  
 Norway Pine 20 inch S73° W 130 feet (Now a 21 inch N Pine S73° W 130 feet)  
 White Pine 18 inch S65° E 150 feet (Now a 24 inch W Pine S65° E 150 feet Scribe overgrown)  
 Angle iron 4 feet x 4 feet x 26 inches N53° E 83.8 feet (Now angle iron N53° E 83.8 feet)  
 G.L.O. state in 1918 they used above information to start resurveys.

and that to perpetuate the location of such corner I did, at the exact location thereof, place a permanent marker consisting of a 6 inch diameter 5 feet long cylindrical concrete monument capped with a 3 inch diameter bronze tablet and stamped

T141N	
R29W	R28W
S25	S30
S36	S31
1965	
R.L.S. No. 6807	

from which reference or witness monuments are located in the manner following:

Red Pine 23 inch N50° W 137.0 feet rescribed S25 BT  
 Red Pine 21 inch S73° W 130.0 feet rescribed S36 BT  
 White Pine 24 inch S65° E 150.0 feet rescribed S31 BT  
 Angle iron N53° E 83.8 feet

Steel sign post 72 inch long set 24 inches in ground with signs 1505 & 54-4 attached  
 N5° W 5.2 feet

All reference bearings are true bearings.

William H. Okernan  
 (Surveyor's Signature)

In the Presence of:  
 E. Farrell Creech  
 Gordon E. Close  
 Subscribed and sworn to before me at CASS LAKE,  
 MINNESOTA  
 this 11th day of December, 1967

GORDON E. CLOSE  
 Notary Public

Notary Public, Cass County, Minn.  
 My Commission expires July 28, 1971

## OFFICE OF REGISTER OF DEEDS

County of Cass

I hereby certify that the within instrument was filed in this office for record on the 28 day of June A.D., 1968 at 9 o'clock AM.

Beverly Hendricks  
 Register of Deeds

By Deputy



SECTION \_\_\_\_\_ TOWNSHIP \_\_\_\_\_ RANGE \_\_\_\_\_ P.M. \_\_\_\_\_

