



-2-

That in order to make the attached AFFIDAVIT AS TO LOCATION OF GOVERNMENT CORNER a matter of public record and locatable by legal description, Affiant does herewith attach said document to this affidavit and requests the Cass County Recorder to record same at her earliest opportunity.

FURTHER, Affiant sayeth not.

Robert Kovanen, Cass County Surveyor

Subscribed and sworn to before me
this 26th day of DEC, 2012.

Notary Public

This instrument was drafted by:

Robert Kovanen
Cass County Surveyor
P.O. Box 579
Walker, MN 56484

AFFIDAVIT AS TO LOCATION OF GOVERNMENT CORNER

Center East 1/16

Corner to Sec. 4 T. 141 N R. 30W No. 213

State of Minnesota, }
 County of Cass } ss.

Peter J. Meyer, being first duly sworn, deposes and says:

That I reside at Cass Lake, Minnesota, and am registered as a Land Surveyor under the laws of the State of Minnesota, having Surveyor's Registration Certificate No. 3628

I further depose and say that on the 28th day of February, 1963, I found the Center East 1/16 corner of Section 4 which was evidenced by the remains of the G.L.O. survey of 1917.

Corner was found to be marked by a 1 inch diameter iron post with a brass cap

stamped: $\begin{matrix} \text{C} & \text{E } 1/16 & \text{C} \\ & \text{S } 4 & \\ & 1917 & \end{matrix}$

Red oak 14 inch $N60\frac{1}{2}^{\circ}E$ 73 links (48.18') (Now a decayed stump at record bearing and distance.)

Red Oak 16 inch $S51\frac{1}{4}^{\circ}W$ 81 links (53.46') (Now a 24 inch red oak at record bearing and distance with blaze facing corner.)

and that to perpetuate the location of such corner I did, at the exact location thereof, place a permanent marker consisting of No new monument set as the G.L.O. brass cap is in good condition.

from which reference or witness monuments are located in the manner following:

Oak 5 inch $S13^{\circ}E$ 19.5 feet marked CE 1/16 BT

Oak 9 inch $N76^{\circ}W$ 52.0 feet marked CE 1/16 BT

Oak 7 inch $N4^{\circ}W$ 65.7 feet marked CE 1/16 BT

Steel sign post 72 inches long, set 24 inches in ground, with standard signs 54-2 and 54-4 attached due West 5.8 feet.

All reference bearings are true bearings.

Peter J. Meyer
 (Surveyor's Signature)

In the Presence of:

Beulah Hendricks
June Ann Nelson

Subscribed and sworn to before me at Walker, Minnesota

this 16 day of September, 19 63

Beulah Hendricks
 Notary Public

Deputy Register of Deeds, Cass County, Minn.

OFFICE OF REGISTER OF DEEDS

County of Cass

I hereby certify that the within instrument was filed in this office for record on the 16 day of September, A.D., 1963 at 9 o'clock A.M.

Leonard P. Peterson
 Register of Deeds

By *Beulah Hendricks* Deputy

SECTION _____ TOWNSHIP _____ RANGE _____ P.M.

