



-2-


That in order to make the attached AFFIDAVIT AS TO LOCATION OF GOVERNMENT CORNER a matter of public record and locatable by legal description, Affiant does herewith attach said document to this affidavit and requests the Cass County Recorder to record same at her earliest opportunity.

FURTHER, Affiant sayeth not.

Robert Kovanen, Cass County Surveyor

Subscribed and sworn to before me
this 26th day of AEC, 2012.

Notary Public



This instrument was drafted by:

Robert Kovanen
Cass County Surveyor
P.O. Box 579
Walker, MN 56484

AFFIDAVIT AS TO LOCATION OF GOVERNMENT CORNER

Section

Corner to Sec.'s 26-27-34-35 T. 141N R. 30W No. 607

State of Minnesota, }
County of Cass } ss.

William H. Okerman, being first duly sworn, deposes and says:

That I reside at Bemidji, Minnesota, and am registered as a Land Surveyor under the laws of the State of Minnesota, having Surveyor's Registration Certificate No. 6807.

I further depose and say that on the 30th day of September, 1964, I found the Section corner of Section's 26-27-34-35

which was evidenced by remains of original government survey of 1873.

Y. Pine 13 inch S45°E 30.36 feet - Now a burned stump at record bearing and distance.

Y. Pine 14 inch N70°E 32.34 feet - Now a burned stump at record bearing and distance.

Y. Pine 9 inch N81°W 29.04 feet - Now a burned stump at record bearing and distance.

Y. Pine 16 inch S41°W 64.68 feet - Now a burned stump at record bearing and distance.

Also found a 2 inch diameter iron pipe at this location.

and that to perpetuate the location of such corner I did, at the exact location thereof, place a permanent marker consisting of a 2 inch diameter 5 feet long galvanized steel pipe filled with concrete and capped with a 3 inch diameter bronze tablet stamped

T141N R30W

S27|S26

S34|S35

1965

R.L.S. No. 6807

from which reference or witness monuments are located in the manner following:

J. Pine 8 inch N53°W 20.3 feet scribed S27 BT

J. Pine 15 inch N22°W 58.3 feet scribed S27 BT

Elm 5 inch N62°E 18.6 feet scribed S26 BT

Oak 6 inch S12°E 6.1 feet scribed S35 BT

Steel sign post 72 inches long set 24 inches in ground with Forest Service signs 54-2 and 54-4 attached due East 7.6 feet.

All reference bearings are true bearings.

William H. Okerman
(Surveyor's Signature)

In the Presence of:

Jayce E. Myher
Clifford B. Linn

Subscribed and sworn to before me at

Cass Lake, Minnesota

this 13th day of May, 1970

Jordan E. Blue
Notary Public

My commission expires July 28, 1971

OFFICE OF REGISTER OF DEEDS

County of Cass

I hereby certify that the within instrument was filed in this office for record on the 19th

day of February A.D., 1971

at 9 o'clock A.M.

Beverly Lindrick
Register of Deeds

By Deputy



SECTION _____ TOWNSHIP _____ RANGE _____ P.M. _____

