

A000587974

OFFICE OF THE COUNTY RECORDER CASS COUNTY, MINNESOTA CERTIFIED, FILED, AND/OR RECORDED ON

12/28/2012 9:31:00 AM AS DOC #: A000587974 PAGES: 4

REC FEES: 0.00

KATHRYN M. NORBY CASS COUNTY RECORDER

BY KF Dep

AFFIDAVIT BY THE CASS COUNTY SURVEYOR IN REGARD TO A CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

STATE OF MINNESOTA }

SSS

COUNTY OF CASS }

Robert Kovanen, being first duly sworn, deposes and states as follows:

That Affiant is the County Surveyor in and for the County of Cass, in the State of Minnesota;

That in such capacity Affiant has knowledge of the books and records kept in the Office of the County Surveyor in and for the County of Cass, State of Minnesota;

That the attached CERTIFICATE OF LOCATION OF GOVERNMENT CORNER has been found in the Surveyor's records and after checking with the Cass County Recorder, it was determined that the document was never assigned a document number and was never officially recorded in the real estate records or tracted in the tract indexes within said Cass County Recorder's Office;

A000587974

-2-

That in order to make the attached CERTIFICATE OF LOCATION OF GOVERNMENT CORNER a matter of public record and locatable by legal description, Affiant does herewith attach said document to this affidavit and requests the Cass County Recorder to record same at her earliest opportunity.

FURTHER, Affiant sayeth not.

Robert Kovanen, Cass County Surveyor

Subscribed and sworn to before me

this 24 day of 120, 20

Notary Public

ROBERT H. YOCHUM
Notary Public
State of Minnesota
My Commt. Exp. 1.31-2015

This instrument was drafted by:

Robert Kovanen Cass County Surveyor P.O. Box 579 Walker, MN 56484

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

Corner to Sec. 30 25 State of Minnesota, County of I hereby certify that on the 28th day of Dec 1958 I found the 1/4 corner of 25-141-32 & Sec. 30- T. 141- R. 31 which was evidenced by 2x48" inch boiler flue set by Elmer B Horst in 1921 in the Sub-division of Sec. 30-141-31 and I further certify that to perpetuate the location of such corner I did, at the exact location thereof, place a permanent marker consisting of a 2 3/4 x 60" capped Monument filled with concrete I further certify that I established a witness or reference points reference or witness monuments consisting of a Elm tree & 2 Cedar Post which reference or witness monuments are located in the manner following: Elm tree 5 inches in diam bears S 26°39' E38.40 ft Mkd S.30 T.141 R.31 a Cedar Post 4x4x48 inches bears N 82°30' E 14.65 ft Mkd S.30 T.141 R.31 a Cedar Post 4x4x48 inches bears N 62°09' W 8.40 ft Mkd S.25 T.141 R.32 Dated at Walker ... Minn., this...... County Surveyor or Highway Engineer. OFFICE OF REGISTER OF DEEDS County of I hereby certify that the within instrument was filed in this office for record on the 22 A. D. 19 60 at 9

Register of Deeds.

Deputy.

Page 4 of 4 A000587974

