AFFIDAVIT BY THE CASS COUNTY SURVEYOR IN REGARD TO A CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

STATE OF MINNESOTA   }

                                            } ss

COUNTY OF CASS   }

Robert Kovanen, being first duly sworn, deposes and states as follows:

That Affiant is the County Surveyor in and for the County of Cass, in the State of Minnesota;

That in such capacity Affiant has knowledge of the books and records kept in the Office of the County Surveyor in and for the County of Cass, State of Minnesota;

That the attached CERTIFICATE OF LOCATION OF GOVERNMENT CORNER has been found in the Surveyor's records and after checking with the Cass County Recorder, it was determined that the document was never assigned a document number and was never officially recorded in the real estate records or tracted in the tract indexes within said Cass County Recorder's Office;

-2-

That in order to make the attached CERTIFICATE OF LOCATION OF GOVERNMENT CORNER a matter of public record and locatable by legal description, Affiant does herewith attach said document to this affidavit and requests the Cass County Recorder to record same at her earliest opportunity.

FURTHER, Affiant sayeth not.

_____
Robert Kovanen, Cass County Surveyor

Subscribed and sworn to before me
this 2nd day of Jan. , 20 13 .

_____
Notary Public

SUSANNE GRAY
Deputy Auditor, Cass County Minnesota
Notarial Officer (ex-officio notary public)
My term is indeterminate

This instrument was drafted by:

Robert Kovanen
Cass County Surveyor
P.O. Box 579
Walker, MN 56484

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

Quarter
Corner to Sec.'s 9 - 16   T. 141 North   R. 28 West   No. 878

State of Minnesota, }ss.

County of   Cass

     I hereby certify that on the ......20th...... day of ......January...... 19..72

I found the ......Quarter...... corner of ......Sections 9 - 16......

which was evidenced by remains of the General Land Office survey of 1918 and documented in

Forest Service Record. ,

and I further certify that to perpetuate the location of such corner, I did, at the exact location thereof, place

a permanent marker consisting of no new monument set as G.L.O. monument is in good condition.

     I further certify that I established ......

reference or witness monuments consisting of ......

which reference or witness monuments are located in the manner following:

Oak 6 inch S7°E   3.80 feet scribed ¼ S16 BT

J. Pine 14 inch N77°W 31.70 feet scribed ¼ S9 BT

J. Pine 11 inch S84°E 49.30 feet scribed ¼ S16 BT

Steel sign post 72 inches long due East 6.60 feet with Forest Service signs 54-2 and 54-4

attached.

Dated at ......Cass Lake...... , Minn., this ...29th... day of ...September... 19 73

William H. Okerman

~~County Surveyor or Highway Engineer.~~
William H. Okerman
Minnesota Registered Land Surveyor No 6807

OFFICE OF REGISTER OF DEEDS }

County of *Cass*

     I hereby certify that the within instrument was filed in this office for record on the ...5th...

day of *February* A. D. 19 74 at 9 o'clock A. M.

Beulah Hendricks

Register of Deeds.

By *BJK* ......Deputy.

SECTION_____ TOWNSHIP_____ RANGE_____ P.M.

	NW.		NE.	
	SW.		SE.	

Top scale: 20 rods 40 " 60 " 80 " 60 " 40 " 20 " 0 " 20 " 40 " 60 " 80 " 60 " 40 " 20 "

Left scale: rods 20 | " 40 | " 60 | " 80 | " 60 | " 40 | " 20 | " 0 | " 20 | " 40 | " 60 | " 80 | " 60 | " 40 | " 20

Right scale: 20 rods | 40 " | 60 " | 80 " | 60 " | 40 " | 20 " | 0 " | 20 " | 40 " | 60 " | 80 " | 60 " | 40 " | 20 "

Bottom scale: rods 20 40 60 80 60 40 20 0 20 40 60 80 60 40 20