

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

East Quarter Corner of Section 19, Township 143 N., Range 25 W., 5th P.M.
State of Minnesota, County of Cass

At the corner location shown on the sketch:

On _____ found _____

- left monument as found
- lowered monument
- removed monument (explain)

On 12-10-2012 placed a 3/4" iron pipe with a plastic cap stamped RLS 21367,
1" above ground level.

SKETCH OF REFERENCE TIES (NOT TO SCALE)



SE1/4-NE1/4,
SECTION 19,
T143N, R25W

SW1/4-NW1/4,
SECTION 20,
T143N, R25W

Set New Tie:
Set nail in northerly face of a twin
8" Cedar, 12" above ground.

Set New Tie:
Set nail in westerly face of a 12"
Cedar, 12" above ground.

Set New Tie:
Set nail in northerly face of a 12"
Spruce, 12" above ground.

NE1/4-SE1/4,
SECTION 19,
T143N, R25W

GOV'T LOT 2,
SECTION 20,
T143N, R25W

NOTE: All bearings are true.

Statement of evidence relative to this corner location is on the back of this page.

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly Licensed land Surveyor under the laws of the State of Minnesota. I further certify that this united States public land survey monument record is correct and complete to the best of my knowledge and belief.

Terry L. Freeman, Land Surveyor

Date 12/28/12 MN License No. 21367



A000589931

OFFICE OF THE COUNTY RECORDER
CASS COUNTY, MINNESOTA
CERTIFIED, FILED, AND/OR
RECORDED ON

2/25/2013 3:31:47 PM

AS DOC #: A000589931

PAGES: 2

REC FEES: 0.00

KATHRYN M. NORBY
CASS COUNTY RECORDER

BY SR _____ Dep



STATEMENT ON EVIDENCE

East Quarter Corner of Section 19, Township 143 North, Range 25 West of the 5th Principal Meridian.

In 1872, Hayward & Griffin, U.S. Deputy Surveyors set a wood post to mark the corner location and established bearing trees as follows: a 6" Spruce N 43° E 10 links a 5" Birch S 38° W 8 links.

In 1965, James Ekstrom, U.S. Forest Service personnel, searched for corner, but found nothing. Information on file in the U.S.F.S. Cass Lake Office T143N R25W Book 2, page 39.

In 1976, Louis D. Gilbert, U.S. Surveyor for the BLM, made a dependent resurvey of part of the township and set a 2½ x 28" aluminum post with stamped cap at the lost, single proportionate position and marked the following bearing trees: 5" Cedar S 19° E 37 links and 7" Cedar N 4° W 33.5 links. Information on file in the Cass County Surveyors Office.

In 2004, Terry L. Freeman, (Landecker & Associates) RLS #21367, performs a survey in Section 20 and shows an iron pipe set. (No BLM monument or accessories was found.)

In 2009, Laverne Leuelling, (Northern Lights Surveying & Mapping) RLS #16089, performs a survey in Section 20 and shows he found the iron set lost in 2004 by Landecker & Assoc.

On October 26, 2012, a Northern Engineering & Consulting survey crew searched for the 1976 BLM information and found nothing. They set a 3/4" iron pipe with plastic cap stamped "RLS 21367" and marked 3 new ties as shown on front of this certificate. I accept the position at the lost, single proportionate position between the NW and NE corners of Section 19.

County Coordinates (Cass County North)

| | |
|----------|------------|
| Northing | 239332.901 |
| Easting | 583420.529 |