




That in order to make the attached AFFIDAVIT AS TO LOCATION OF GOVERNMENT CORNER a matter of public record and locatable by legal description, Affiant does herewith attach said document to this affidavit and requests the Cass County Recorder to record same at her earliest opportunity.


FURTHER, Affiant sayeth not.



Robert Kovanen, Cass County Surveyor

Subscribed and sworn to before me
this 26th day of Feb., 20 13.





Notary Public

This instrument was drafted by:

Robert Kovanen
Cass County Surveyor
P.O. Box 579
Walker, MN 56484

AFFIDAVIT AS TO LOCATION OF GOVERNMENT CORNER

Section
Corner to Sec.'s 9-10-15-16 T. 144N R. 27W No. 407

State of Minnesota, }
County of Cass } ss.

William H. Okerman, being first duly sworn, deposes and says:
That I reside at Bemidji, Minnesota, and am registered as a Land Surveyor under the laws of the State of Minnesota, having Surveyor's Registration Certificate No. 6807.
I further depose and say that on the 16th day of June, 1966, I found the Section corner of Section's 9-10-15-16 which was evidenced by G.L.O. resurvey of 1937 a set concrete monument 2 feet long 6 inches diameter with brass cap marked T144N R27W
Tamarack 8 inch N69-3/4° E 64 links or 42.24 feet - Now a dead Tamarack at S 9 S10 correct bearing and distance - scribe visible. S16 S15
Poplar 12 inch S87° E 211 links or 139.26 feet - Now a dead rotted log at 1937 correct bearing and distance - scribe visible.
White Pine 8 inch S79 1/4° W 223 links or 147.18 feet - Now a dead White Pine at correct bearing and distance - scribe visible.
Red Pine 14 inch N86 1/2° W 222 links or 146.52 feet - Now a 20 inch Pine at correct bearing and distance - scribe overgrown.
and that to perpetuate the location of such corner I did, at the exact location thereof, place a permanent marker consisting of no new marker set, used G.L.O. brass cap.

from which reference or witness monuments are located in the manner following:
G.L.O. Red Pine 20 inch N86 1/2° W 146.52 feet - rescribed S9 BT.

Spruce 8 inch S62° W 176.3 feet - scribed S16 BT.

Tamarack 10 inch N18° W 74.3 feet - scribed S9 BT.

Balsam 16 inch N84° E 137.0 feet - scribed S10 BT.

Poplar 12 inch S72° E 147.5 feet - scribed S15 BT.

Set a steel sign post 72 inches long with signs 54-2 and 54-4 attached due North 7.4 feet. All reference bearings are true bearings.

William H. Okerman
(Surveyor's Signature)

In the Presence of:
Beulah Hendricks
Claudine Taylor
Subscribed and sworn to before me at
Walker, Minnesota

this 17 day of November, 1966

Beulah Hendricks
- Notary Public

Register of Deeds, Cass County, Minn.

OFFICE OF REGISTER OF DEEDS

County of Cass

I hereby certify that the within instrument was filed in this office for record on the 17 day of November, A.D., 1966 at 9 o'clock A.M.

Beulah Hendricks
Register of Deeds

By Deputy



SECTION _____ TOWNSHIP _____ RANGE _____ P.M. _____

