

000590073

OFFICE OF THE COUNTY RECORDER CASS COUNTY, MINNESOTA CERTIFIED, FILED, AND/OR RECORDED ON

2/26/2013 2:13:01 PM
AS DOC #: A000590073
PAGES: 4
REC FEES: 0.00
KATHRYN M. NORBY
CASS COUNTY RECORDER
BY SR Dep

## AFFIDAVIT BY THE CASS COUNTY SURVEYOR IN REGARD TO AN AFFIDAVIT AS TO LOCATION OF A GOVERNMENT CORNER

Robert Kovanen, being first duly sworn, deposes and states as follows:

That Affiant is the County Surveyor in and for the County of Cass, in the State of Minnesota;

That in such capacity Affiant has knowledge of the books and records kept in the Office of the County Surveyor in and for the County of Cass, State of Minnesota;

That the attached AFFIDAVIT AS TO LOCATION OF GOVERNMENT CORNER has been found in the Surveyor's records and after checking with the Cass County Recorder, it was determined that the document was never assigned a document number and was never officially recorded in the real estate records or tracted in the tract indexes within said Cass County Recorder's Office;



That in order to make the attached AFFIDAVIT AS TO LOCATION OF GOVERNMENT CORNER a matter of public record and locatable by legal description, Affiant does herewith attach said document to this affidavit and requests the Cass County Recorder to record same at her earliest opportunity.

-2-

FURTHER, Affiant sayeth not.

Robert Kovanen, Cass County Surveyor

Subscribed and sworn to before me this 26th day of 3eb

Notary Public

Deputy Auditor. Cass County Minnesota

This instrument was drafted by:

Robert Kovanen Cass County Surveyor P.O. Box 579 Walker, MN 56484

## AFFIDAVIT AS TO LOCATION OF GOVERNMENT CORNER

				 I COMMITTEE	
Quarter Corner to	Sec!s 24 - 19	T	<u> Դե</u> լե N	 W & 26 Wyo. 4/3	
	Minnesota,				
County of	Cass	88.			

William H. Okerman That I reside at Bemidji					the
laws of the State of Minnesota, having Surv				egor unaer	une
I further depose and say that on the		•			6
I found the Quarter corner of					
which was evidenced by G.L.O. r a set iron post 3 feet long by 1 inc	esurvey of	1937			./4
White Pine 6 inch N57°E 10 lks or 6 correct bearing and distance - bla		Now a 12 inch W	hite Pine at	<b>S</b> 24	<b>S</b> 19
Cedar 6 inch S1920W 39 lks or 25.74 bearing and distance - scribe visi	feet - Now	a ll inch Ceda	r at correct	19	37
and that to perpetuate the location of such co consisting ofNo new marker set, used			hereof, place a perm	ranent mar	ker

from which reference or witness monuments are located in the manner following: G.L.O. White Pine 12 inch N57°E 6.60 feet - rescribed 1/4 S19 BT.

Set a steel sign post 72 inches long with signs 54-4 and 54-2 attached due West 4.7 feet.

All reference bearings are true bearings.

William & Herman	_
(Surveyor's Signature)	
In the Presence of	
In the Presence of:	
and the second s	low
Subscribed and Hours to before me at	
Walker, Pinnable,	•••••
this 17th day of 18teater	19.66
Beulah Hendricks	
Notary Public -	

Register of Deeds, Cass County, Minn.

OFFICE OF REGISTER OF DEEDS
County ofCass
I hereby certify that the within instrument was filed in this office for record on the 17th
day of November A.D., 19 66
at9o'clogod
Beulet Din duck
Register of Deeds
ByDeputy



