



-2-

That in order to make the attached AFFIDAVIT AS TO LOCATION OF GOVERNMENT CORNER a matter of public record and locatable by legal description, Affiant does herewith attach said document to this affidavit and requests the Cass County Recorder to record same at her earliest opportunity.

FURTHER, Affiant sayeth not.

Robert Kovanen, Cass County Surveyor

Subscribed and sworn to before me
this 26th day of Feb., 2013.

Susanne Gray
Notary Public



This instrument was drafted by:

Robert Kovanen
Cass County Surveyor
P.O. Box 579
Walker, MN 56484

AFFIDAVIT AS TO LOCATION OF GOVERNMENT CORNER 399

Section 24-25 T. 144N R. 26W No.
 Corner to Sec.'s 19-30 T. 144N R. 26W No.

State of Minnesota, }
 County of Cass } ss.

William H. Okerman, being first duly sworn, deposes and says:

That I reside at Bemidji, Minnesota, and am registered as a Land Surveyor under the laws of the State of Minnesota, having Surveyor's Registration Certificate No. 6807.

I further depose and say that on the 23rd day of June, 1966, I found the Section corner of Section's 24-25-19-30

which was evidenced by G.L.O. resurvey of 1937
 a set concrete monument 2 feet long 6 inches in diameter with brass cap marked
 White Pine 26 inch N66 $\frac{1}{4}$ °E 46 links or 30.36 feet - Now a 27 inch White Pine at
 correct bearing and distance - scribe visible - marked T144N R26E S19 BT. T144N
R27W R26W
S24 S19
S25 S30
1937
 Original white pine 20 inch S28°E 10.56 feet - Now a 26 inch White Pine at
 correct bearing and distance - scribe visible - old tag attached to this tree.
 Spruce 14 inch S61 $\frac{1}{2}$ °W 52 links or 34.32 feet - Now a Spruce stump at correct
 bearing and distance - scribe visible - marked T144N R27W S25 BT.
 Birch 10 inch N27°W 64 links or 42.24 feet - Now a 16 inch Birch at correct
 bearing and distance - scribe visible - marked T144N R27 W S24 BT.
 and that to perpetuate the location of such corner I did, at the exact location thereof, place a permanent marker
 consisting of no new marker set, used G.L.O. brass cap.

from which reference or witness monuments are located in the manner following:

Original White Pine 26 inch S28°E 10.56 feet - added BT at base of tree.

Birch 10 inch S30°W 15.22 feet - scribed S25 BT.

Set a steel sign post 72 inches long with signs 54-4 and 54-2 attached due West 3.7 feet.

All reference bearings are true bearings.

William H. Okerman
 (Surveyor's Signature)
 In the Presence of:
Bessie Hendricks
Charles Taylor
 Subscribed and sworn to before me at
 Walker, Minnesota
 this 17th day of November, 1966
Bessie Hendricks
 -- Notary Public

Register of Deeds, Cass County, Minn.

OFFICE OF REGISTER OF DEEDS

County of Cass

I hereby certify that the within instrument was
 filed in this office for record on the 17th
 day of November, A.D., 1966
 at 9 o'clock A.M.

Bessie Hendricks
 Register of Deeds

By Deputy



SECTION _____ TOWNSHIP _____ RANGE _____ P.M. _____

