




That in order to make the attached AFFIDAVIT AS TO LOCATION OF GOVERNMENT CORNER a matter of public record and locatable by legal description, Affiant does herewith attach said document to this affidavit and requests the Cass County Recorder to record same at her earliest opportunity.

FURTHER, Affiant sayeth not.

Robert Kovanen, Cass County Surveyor

Subscribed and sworn to before me
this 26th day of Feb., 2013.

Notary Public



This instrument was drafted by:

Robert Kovanen
Cass County Surveyor
P.O. Box 579
Walker, MN 56484

AFFIDAVIT AS TO LOCATION OF GOVERNMENT CORNER

Section
Corner to Sec.'s 19-20-29-30 T. 143N R. 26W No. 579State of Minnesota, }
County of Cass }^{ss.}

William H. Okerman, being first duly sworn, deposes and says:

That I reside at Bemidji, Minnesota, and am registered as a Land Surveyor under the laws of the State of Minnesota, having Surveyor's Registration Certificate No. 6807.

I further depose and say that on the 2nd day of October, 1969, I found the Section corner of Sections 19-20-29-30 which was evidenced by remains of the original Government survey of 1872.

Fir 5 inch S23°E 9.90 feet - not found

Spruce 10 inch S22°W 13.86 feet - not found

Maple 6 inch N45°E 19.80 feet - not found

W. Pine 26 inch N48°W 36.96 feet - found in 1919 as burned stump BT shown
Cass County survey of 1915 by John Curo, Book B, Page 84.Cedar 12 inch N61°18'E 66.6 feet - now down and decayed log at record bearing
and distance.

(see reverse)

and that to perpetuate the location of such corner I did, at the exact location thereof, place a permanent marker consisting of a 2 inch diameter, 5 foot long galvanized steel pipe filled with concrete and capped with a 3 inch diameter brass tablet stamped:

T143N R26W

S19|S20

S30|S29

1969

R.L.S. No.6807

from which reference or witness monuments are located in the manner following:

W. Oak 7 inch S67°E 54.40 feet scribed S29 BT

W. Oak 10 inch S16°W 66.45 feet scribed S30 BT

W. Oak 5 inch N57°W 49.90 feet scribed S19 BT

Elm 8 inch N15°E 37.50 feet scribed S20 BT

Steel sign post 72 inches long due north 2.5 feet with Forest Service signs 54-2 and 54-4 attached.

All reference bearings are true bearings.

William H. Okerman
(Surveyor's Signature)

In the Presence of:

Joyce E. Miller
Clifford E. MillerSubscribed and sworn to before me at
Cass Lake, Minnesota

this 28th day of February, 1970

Gordon E. Close
Notary PublicGORDON E. CLOSE
Notary Public, Cass County, Minn.
My commission expires July 28, 1971

OFFICE OF REGISTER OF DEEDS

County of Cass

I hereby certify that the within instrument was filed in this office for record on the 5th day of February, A.D., 1971 at 9:30 a.m.

Benedict Handrick
Register of Deeds

By Deputy

W. Oak 18 inch S32°E 41.7 feet - now a stump at record bearing and distance.
 Ironwood 6 inch S72°30'W 47.3 feet - not found.
 Basswood 12 inch N59°43'W 36.2 feet - now stump-hole at record bearing and distance.
 Cass County Survey of 1919 by James H. Flynn.
 Set iron monument - found 2 inch iron monument with capped marked
 W. Oak 18 inch S35°45'E 45 feet - not found.
 Basswood 12 inch N66°W 34 feet - not found.

19 20
 30 29

SECTION _____ TOWNSHIP _____ RANGE _____ P.M. _____

