



That in order to make the attached AFFIDAVIT AS TO LOCATION OF GOVERNMENT CORNER a matter of public record and locatable by legal description, Affiant does herewith attach said document to this affidavit and requests the Cass County Recorder to record same at her earliest opportunity.

FURTHER, Affiant sayeth not.

Robert Kovanen, Cass County Surveyor

Subscribed and sworn to before me this 27th day of Feb., 2013.



Notary Public

This instrument was drafted by:

Robert Kovanen
Cass County Surveyor
P.O. Box 579
Walker, MN 56484



-2-

That in order to make the attached AFFIDAVIT AS TO LOCATION OF GOVERNMENT CORNER a matter of public record and locatable by legal description, Affiant does herewith attach said document to this affidavit and requests the Cass County Recorder to record same at her earliest opportunity.


FURTHER, Affiant sayeth not.



Robert Kovanen, Cass County Surveyor

Subscribed and sworn to before me
this 27th day of Feb., 2013.





Notary Public

This instrument was drafted by:

Robert Kovanen
Cass County Surveyor
P.O. Box 579
Walker, MN 56484

AFFIDAVIT AS TO LOCATION OF GOVERNMENT CORNER

Corner to Sec 1-2-35-36 T. 115 - 116 N R. 27 W No. 176

State of Minnesota, }
County of Cass } ss.

Peter J. Meyer, being first duly sworn, deposes and says:

That I reside at Cass Lake, Minnesota, and am registered as a Land Surveyor under the laws of the State of Minnesota, having Surveyor's Registration Certificate No. 3628.

I further depose and say that on the 11th day of September, 1962, I found the Section corner of sections 1 - 2 - 35 - 36 which was evidenced by the remains of three bearing trees from the original Government survey of 1874.

Norway Pine 30" 19 links or 12.54 feet (Now a stump hole East 12.54')

Norway Pine 14" S36°W 103 links or 67.98 feet (Now a 18" windfall scribed T115N R27W at record bearing and distance)

Norway Pine 28" N20°W 95 links or 62.70 feet (Now a pine stump mostly decayed at record bearing and distance)

and that to perpetuate the location of such corner I did, at the exact location thereof, place a permanent marker consisting of a 2 inch inside diameter, 5 foot long, galvanized wrought iron pipe filled with concrete and capped with a 3 inch diameter bronze tablet stamped:-

T116N	R27W
S35	S36
S 2	S 1
T115N	
1962	
RLS No. 3628	

from which reference or witness monuments are located in the manner following:

Red Pine 9" N33½°E 44.35 feet marked S36 BT

Red Pine 11" N50°W 61.5 feet marked S35 BT

Black spruce 5" S10°E 70.4 feet marked S1 PT

Steel sign post 72" long, set 24" in ground with signs 54-2 and 54-4 attached S78½°W 3.07 feet.

All reference bearings are true bearings.


 (Surveyor's Signature)

In the Presence of:

Beulah Hendricks

June Ann Nelson

Subscribed and sworn to before me at

Walter, Minnesota

this 16 day of September, 19 63

Beulah Hendricks

Notary Public

Deputy Register of Deeds, Cass County, Minn.

OFFICE OF REGISTER OF DEEDS

County of Cass

I hereby certify that the within instrument was filed in this office for record on the 16 day of September, A.D., 19 63

at 9 o'clock A.M.


 Register of Deeds

By Beulah Hendricks Deputy



SECTION _____ TOWNSHIP _____ RANGE _____ P.M. _____

