

A000590128

OFFICE OF THE COUNTY RECORDER CASS COUNTY, MINNESOTA CERTIFIED, FILED, AND/OR RECORDED ON

2/27/2013 10:51:27 AM
AS DOC #: A000590128
PAGES: 4
REC FEES: 0.00
KATHRYN M. NORBY
CASS COUNTY RECORDER

BY\_MW\_\_\_Dep

## AFFIDAVIT BY THE CASS COUNTY SURVEYOR IN REGARD TO AN AFFIDAVIT AS TO LOCATION OF A GOVERNMENT CORNER

STATE OF MINNESOTA	}
	}ss
COUNTY OF CASS	}

Robert Kovanen, being first duly sworn, deposes and states as follows:

That Affiant is the County Surveyor in and for the County of Cass, in the State of Minnesota;

That in such capacity Affiant has knowledge of the books and records kept in the Office of the County Surveyor in and for the County of Cass, State of Minnesota;

That the attached AFFIDAVIT AS TO LOCATION OF GOVERNMENT CORNER has been found in the Surveyor's records and after checking with the Cass County Recorder, it was determined that the document was never assigned a document number and was never officially recorded in the real estate records or tracted in the tract indexes within said Cass County Recorder's Office;



That in order to make the attached AFFIDAVIT AS TO LOCATION OF GOVERNMENT CORNER a matter of public record and locatable by legal description, Affiant does herewith attach said document to this affidavit and requests the Cass County Recorder to record same at her earliest opportunity.

FURTHER, Affiant sayeth not.

Robert Kovanen, Cass County Surveyor

Subscribed and sworn to before me

this 27 day of Feb.

, 20<u>13</u>

SUSANNE GRAY
Deputy Auditor, Cass County Minnesota
Notarial Officer (ex-officio notary public)
My term is indeterminate

Notary Public

This instrument was drafted by:

Robert Kovanen Cass County Surveyor P.O. Box 579 Walker, MN 56484

## AFFIDAVIT AS TO LOCATION OF GOVERNMENT CORNER

	2 - 11	•	<i>T</i> . 1	45 N	R.	27 W		26
State of Min	inesota.							
unty of Cass	\{\epsilon \} \( \epsilon \)	88.						
P	eter J. Mey	rer		, being	first duly	sworn, depose	es and says	::
That I reside at	Cass Lake	<b>1</b>	, Minneso	ota, $an$	d am regis	$oldsymbol{tered}$ as a $La$	nd Surveyo	r under the
vs of the State of	Minnesota, h	aving Surv	veyor's Regi	stration Ce	ertificate $N$	o. 3628	•••••	
$I\ further\ depose$	and say that	on the	25th		day of	November		, <i>19</i> 58
found the								
ich was evidenced	by two re	maining o	original s	scribed b	pearing t	rees of the	e Governm	ent Survey
f 1873. l) 4 inch Tamar 46.2 feet.	ack (now 5	inch dead	d stub wit	th s <b>cri</b> bi	ing <b>visi</b> bi	le) N 65 <sup>0</sup> V	V, 70 lin	ks or
2) 3 inch tamar	ack (now 5	inch wind	ifall with	h scribin	ng visible	e) Ѕ 40 <sup>0</sup> W,	, 38 link	s or 25.1
checked and fo								
d that to permetua	t. the location	· · · · · · · · · · · · · · · · · · ·						
ed that to perpetua				at the exa				
nd that to perpetuansisting ofa 2 in oncrete and cap	nch inside	diameter,	, 5 foot ]	at the exa long galv	ranized w:	rought iron		
nsisting of a 2 i	nch inside	diameter, 3 inch di T 1	, 5 foot ] Lameter br 45 N R	at the exa long galv	ranized w:	rought iron		
nsisting of a 2 i	nch inside	diameter, 3 inch di T 1	, 5 foot ] iameter bi 45 N R 4 2-11	at the exa long galv	ranized w:	rought iron		
nsisting of a 2 i	nch inside	diameter, 3 inch di T 1/1	, 5 foot 1 iameter br 45 N R 4 2-11 1958	at the exa long galv ronze tab 27 W	ranized w:	rought iron		
nsisting of <u>a 2 i</u> oncrete and cap	nch inside ped with a	diameter, 3 inch di T 1 1/l R.	, 5 foot 1 iameter br 45 N R 4 2-11 1958 .L.S. 3628	at the exa long galv ronze tab 27 W	vanized w Dlet stam	rought iron		
nsisting of a 2 increte and cap	nch inside ped with a  e or witness m	diameter, 3 inch di T 11 1/1 R. conuments d	, 5 foot 1 iameter br 45 N R 4 2-11 1958 .L.S. 3628 are located	at the exa long galv ronze tab 27 W	vanized w Dlet stam	rought iron		
oncrete and cap	nch inside ped with a e or witness m S $h0^{\frac{1}{5}0}$	diameter, 3 inch di T 1/1 1/1 R. conuments c	, 5 foot 1 iameter br 45 N R 4 2-11 1958 .L.S. 3628 are located	at the exa long galv ronze tab 27 W	vanized w Dlet stam	rought iron		
oncrete and cap	nch inside ped with a e or witness m S $h0^{\frac{1}{5}0}$	diameter, 3 inch di T 1/1 1/1 R. conuments c	, 5 foot 1 iameter br 45 N R 4 2-11 1958 .L.S. 3628 are located	at the exa long galv ronze tab 27 W	vanized w Dlet stam	rought iron		
oncrete and cap om which reference inch tamarack inch B. Spruce inch B. Spruce	nch inside ped with a e or witness m  S $40^{\frac{1}{2}0}$ e S $68^{\circ}$ e N $11^{\frac{1}{2}0}$	diameter, 3 inch di T 11 1/1 R. conuments d W 33.7 W 50.3	iameter br iameter br i5 N R i 2-11 1958 L.S. 3628 are located 2 feet 7 feet 3 feet	at the exa long galv ronze tab 27 W	vanized w Dlet stam	rought iron		
om which references inch B. Spruces inch B. Spruces inch B. Spruces	nch inside ped with a e or witness m  S $40^{\frac{1}{2}0}$ e S $68^{\circ}$ e N $11^{\frac{1}{2}0}$	diameter, 3 inch di T 11 1/1 R. conuments d W 33.7 W 50.3	iameter br iameter br i5 N R i 2-11 1958 L.S. 3628 are located 2 feet 7 feet 3 feet	at the exa long galv ronze tab 27 W	vanized w Dlet stam	rought iron		
om which reference inch B. Spruce inch B. Spruce	nch inside ped with a e or witness m  S $40^{\frac{1}{2}0}$ e S $68^{\circ}$ e N $11^{\frac{1}{2}0}$	diameter, 3 inch di T 11 1/1 R. conuments d W 33.7 W 50.3	iameter br iameter br i5 N R i 2-11 1958 L.S. 3628 are located 2 feet 7 feet 3 feet	at the exa long galv ronze tab 27 W	vanized w Dlet stam	rought iron		
om which reference inch B. Spruce inch B. Spruce	nch inside ped with a e or witness m  S $40^{\frac{1}{2}0}$ e S $68^{\circ}$ e N $11^{\frac{1}{2}0}$	diameter, 3 inch di T 11 1/1 R. conuments d W 33.7 W 50.3	iameter br iameter br i5 N R i 2-11 1958 L.S. 3628 are located 2 feet 7 feet 3 feet	at the exa long galv ronze tab 27 W	vanized w Dlet stam	rought iron		
nsisting of a 2 increte and cap	nch inside ped with a e or witness m  S $40^{\frac{1}{2}0}$ e S $68^{\circ}$ e N $11^{\frac{1}{2}0}$	diameter, 3 inch di T 11 1/1 R. conuments d W 33.7 W 50.3	iameter br iameter br i5 N R i 2-11 1958 L.S. 3628 are located 2 feet 7 feet 3 feet	at the exa long galv ronze tab 27 W	vanized w Dlet stam	rought iron		
om which reference inch B. Spruce inch B. Spruce	nch inside ped with a e or witness m  S $40^{\frac{1}{2}0}$ e S $68^{\circ}$ e N $11^{\frac{1}{2}0}$	diameter, 3 inch di T 11 1/1 R. conuments d W 33.7 W 50.3	iameter br iameter br i5 N R i 2-11 1958 L.S. 3628 are located 2 feet 7 feet 3 feet	at the exa long galv ronze tab 27 W	vanized w Dlet stam	rought iron		
om which reference inch B. Spruce inch B. Spruce	nch inside ped with a e or witness m  S $40^{\frac{1}{2}0}$ e S $68^{\circ}$ e N $11^{\frac{1}{2}0}$	diameter, 3 inch di T 11 1/1 R. conuments d W 33.7 W 50.3	iameter br iameter br i5 N R i 2-11 1958 L.S. 3628 are located 2 feet 7 feet 3 feet	at the exa long galv ronze tab 27 W	vanized w Dlet stam	rought iron		
om which reference inch B. Spruce inch B. Spruce	nch inside ped with a e or witness m  S $40^{\frac{1}{2}0}$ e S $68^{\circ}$ e N $11^{\frac{1}{2}0}$	diameter, 3 inch di T 11 1/1 R. conuments d W 33.7 W 50.3	iameter br iameter br i5 N R i 2-11 1958 L.S. 3628 are located 2 feet 7 feet 3 feet	at the exa long galv ronze tab 27 W	vanized with the stamp	rought iron ped:	n pipe fi	
om which reference inch tamarack inch B. Spruce inch B. Spruce All reference be	nch inside ped with a e or witness m  S $40^{\frac{1}{2}0}$ e S $68^{\circ}$ e N $11^{\frac{1}{2}0}$	diameter, 3 inch di T 11 1/1 R. onuments o  E 33.2 W 33.7 W 50.3	iameter br iameter br i5 N R i 2-11 1958 L.S. 3628 are located 2 feet 7 feet 3 feet	at the exalong galveronze take 27 W  8 in the man	vanized word stam	rought iron	DEEDS	

Total Meyer
(Surveyor's Signature)
In the Presence of:
Bulgh Hevarer
Subscribed and sworn to before me at
this day of ,19
Notary Public Register of Deeds

			rd on the	n instrum 14th	ient was
ay of	June		ka i		1960
t	9 o'ol	ock * 1	iz ; ;		
L	maril	D	Setira	<b>.</b>	
	78	Regist	er of Dece	8,	
Ru		•			Deputy



Page 4 of 4 A0005

