



That in order to make the attached AFFIDAVIT AS TO LOCATION OF GOVERNMENT CORNER a matter of public record and locatable by legal description, Affiant does herewith attach said document to this affidavit and requests the Cass County Recorder to record same at her earliest opportunity.

FURTHER, Affiant sayeth not.

Robert Kovanen, Cass County Surveyor

Subscribed and sworn to before me
this 27th day of Feb., 2013.

Notary Public



This instrument was drafted by:

Robert Kovanen
Cass County Surveyor
P.O. Box 579
Walker, MN 56484

AFFIDAVIT AS TO LOCATION OF GOVERNMENT CORNER

Corner to Sec. 20 - 21 T. 145 N. R. 27 W. No. 10

State of Minnesota, }
County of Cass } ss.

Peter J. Meyer, being first duly sworn, deposes and says:
That I reside at Cass Lake, Minnesota, and am registered as a Land Surveyor under the laws of the State of Minnesota, having Surveyor's Registration Certificate No. 3628.
I further depose and say that on the 3rd day of December, 1958, I found the 1/4 corner of sections 20-21 which was evidenced by two remaining original bearing trees of the Government Survey of 1873; one remaining scribed bearing tree from the recovery survey by J. A. Gjelhaug, Jr., Civil Engineer, U. S. Forest Service, 1937.
(1) 8 inch Red Pine N. 80° E. (now 10 inch burnt stump with no scribing visible) now S. 80° E., 8 links or 5.2 feet.
(2) 10 inch Red Pine (now 11 inch burnt stump with no scribing visible) S. 45° W., 14 links or 9.2 feet.
(3) Recovery notes 5 inch Jack Pine (now 10 inch with scribing visible) N. 55° E., 61 links or 40.3 feet. Corner was found to be marked by 3 inch scribed stake.
and that to perpetuate the location of such corner I did, at the exact location thereof, place a permanent marker consisting of a 2 inch inside diameter, 5 foot long galvanized wrought iron pipe filled with concrete and capped with a 3 inch diameter bronze tablet stamped:

T. 145 N. R. 27 W.
1/4 20-21
1958

R.L.S. 3628

from which reference or witness monuments are located in the manner following:

Section 20	12" R. Pine	N. 56 $\frac{1}{2}$ ° W.	57.8 feet
Section 20	7" R. Pine	S. 32° W.	38.4 feet
Section 21	5" R. Pine	N. 84° E.	22.5 feet

All reference bearings are true bearings.

Peter J. Meyer
(Surveyor's Signature)
In the presence of:
L. P. Peterson
Bessie Kevair
Subscribed and sworn to before me at
Walker, Minn.
this 21 day of April, 19 60
Bessie Kevair
Deputy Register of Deeds

OFFICE OF REGISTER OF DEEDS

County of Cass

I hereby certify that the within instrument was filed in this office for record on the 21 day of April A.D., 19 60 at 9 o'clock A.M.

L. P. Peterson
Register of Deeds

By Deputy



SECTION _____ TOWNSHIP _____ RANGE _____ P.M. _____

