







That in order to make the attached AFFIDAVIT AS TO LOCATION OF GOVERNMENT CORNER a matter of public record and locatable by legal description, Affiant does herewith attach said document to this affidavit and requests the Cass County Recorder to record same at her earliest opportunity.

FURTHER, Affiant sayeth not.

  
\_\_\_\_\_  
Robert Kovanen, Cass County Surveyor

Subscribed and sworn to before me  
this 37 day of February, 2013.

  
\_\_\_\_\_  
Notary Public



This instrument was drafted by:

Robert Kovanen  
Cass County Surveyor  
P.O. Box 579  
Walker, MN 56484

## AFFIDAVIT AS TO LOCATION OF GOVERNMENT CORNER

Section

Corner to Sec's 11-12-13-14 T. 145 N. R. 31 W No. 396

State of Minnesota,

County of Cass }<sup>88.</sup>

William H. Okerman

, being first duly sworn, deposes and says:

That I reside at Bemidji, Minnesota, and am registered as a Land Surveyor under the laws of the State of Minnesota, having Surveyor's Registration Certificate No. 6807.

I further depose and say that on the 30th day of July, 1964,

I found the Section corner of Sections 11-12-13-14 which was evidenced by notes of original Government Survey of 1875.

White Pine 30 inch S22°W 30 lks or 19.8 feet - Now Pine stump S32°W 19.8 feet.

White Pine 20 inch S7°E 68 lks or 44.9 feet - Now 6.5 feet high stump with scribe marks visible at record bearing &amp; distance.

White Pine 12 inch N48°E 68 lks or 44.9 feet - Now stump N45°E 43.0 feet.

(Notes of Forest Engineer Gjelhaug of 1934 - scribed wood post &amp; iron pipe)

Red Oak 4 inch N55°W 7 lks or 4.6 feet - Now a 6 inch Oak N52°W 5.5 feet - scribe overgrown.

Red Oak 4 inch N60½°E 37 lks or 24.4 feet - Now a 8 inch Oak N60½°E 24.4 feet - scribe overgrown.

White Oak 4 inch S88½°E 39 lks or 25.7 feet - Now a 6 inch Oak S88½°E 25.7 feet - scribe overgrown.

Red Oak 4 inch S12°W 29½ lks or 19.5 feet - Now a 8 inch Oak S12°W 19.5 feet - scribe overgrown.

and that to perpetuate the location of such corner I did, at the exact location thereof, place a permanent marker consisting of 6 inch diameter, 60 inch long cylindrical concrete monument capped with a 3 inch diameter bronze tablet stamped

T145N R31W

S11 | S12

S14 | S13

1964

R.L.S. No. 6807

from which reference or witness monuments are located in the manner following:

Gjelhaug survey B.T.'s:

Red Oak 6 inch N52°W 5.5 feet - rescribed B.T.

Red Oak 8 inch N60½°E 24.4 feet - rescribed B.T.

White Oak 6 inch S88½°E 25.7 feet - rescribed B.T.

Red Oak 8 inch S12°W 19.5 feet - rescribed B.T.

All reference bearings are true bearings.

William H. Okerman  
(Surveyor's Signature)

In the Presence of:

Claudie Kaylor  
Beulah Hendrick

Subscribed and sworn to before me at

Walpole Minn.  
this 5th day of July, 1966Claudie Kaylor  
Notary PublicDEPUTY REGISTER OF DEEDS  
CASS COUNTY, MINN.

OFFICE OF REGISTER OF DEEDS

County of Cass

I hereby certify that the within instrument was filed in this office for record on the 5th

day of July A.D., 1966

at 9 o'clock A.M.

Beulah Hendrick  
Register of Deeds

By Deputy



SECTION \_\_\_\_\_ TOWNSHIP \_\_\_\_\_ RANGE \_\_\_\_\_ P.M. \_\_\_\_\_

