






That in order to make the attached AFFIDAVIT AS TO LOCATION OF GOVERNMENT CORNER a matter of public record and locatable by legal description, Affiant does herewith attach said document to this affidavit and requests the Cass County Recorder to record same at her earliest opportunity.

FURTHER, Affiant sayeth not.

Robert Kovanen, Cass County Surveyor

Subscribed and sworn to before me  
this 27 day of February, 2013.

Linda C. Husby  
Notary Public



This instrument was drafted by:

Robert Kovanen  
Cass County Surveyor  
P.O. Box 579  
Walker, MN 56484

## AFFIDAVIT AS TO LOCATION OF GOVERNMENT CORNER

Corner to Sec. 17-18-19-20 T. 145 N. R. 29 W. No. 18

State of Minnesota, }  
 County of Cass } ss.

Peter J. Meyer

, being first duly sworn, deposes and says:

That I reside at Cass Lake, Minnesota, and am registered as a Land Surveyor under the laws of the State of Minnesota, having Surveyor's Registration Certificate No. 3628

I further depose and say that on the 8th day of December, 1958, I found the section corner of sections 17-18-19-20 which was evidenced by two remaining original scribed bearing trees of the Government Survey of 1873.

- (1) 16 inch Red Pine (now 24 inch stump with no scribing visible) N. 14° E., 20 links or 13.2 feet.  
 (2) 10 inch Red Pine (now 16 inch stump with scribing B.T. visible) S. 28° E., 18 links or 11.9 feet.

I checked and found no evidence of original Government corner monument.

and that to perpetuate the location of such corner I did, at the exact location thereof, place a permanent marker consisting of a 6 inch cylindrical concrete monument 5 feet in length, capped with a 3 inch bronze tablet stamped:

T. 145 N. R. 29 W.  
 17-18-19-20  
 1958  
 R.L.S. 3628

from which reference or witness monuments are located in the manner following:

|            |             |                          |           |
|------------|-------------|--------------------------|-----------|
| Section 18 | 13" J. Pine | N. 49° W.                | 45.6 feet |
| Section 19 | 12" J. Pine | S. 43 <sup>10</sup> ° W. | 28.4 feet |
| Section 20 | 10" J. Pine | S. 15° E.                | 37.7 feet |
| Section 20 | 12" J. Pine | S. 80° E.                | 42.0 feet |

All reference bearings are true bearings.

*Peter J. Meyer*  
 (Surveyor's Signature)  
 In the Presence of  
*Bulah Hewner*  
 Subscribed and sworn to before me at  
 Walker, Minn.  
 this 21 day of April, 1960  
*Bulah Hewner*  
 Deputy Register of Deeds

## OFFICE OF REGISTER OF DEEDS

County of Cass

I hereby certify that the within instrument was filed in this office for record on the 21 day of April, A.D., 1960 at 2:06 P.M.

*B. P. Peterson*  
 Register of Deeds  
 By \_\_\_\_\_ Deputy



SECTION \_\_\_\_\_ TOWNSHIP \_\_\_\_\_ RANGE \_\_\_\_\_ P.M. \_\_\_\_\_

