

# CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

East Quarter Corner of Section 32

Township 139 N , Range 28 W , 5th P.M.

STATE OF MINNESOTA, COUNTY OF Cass



**A000591553**

OFFICE OF THE COUNTY RECORDER  
CASS COUNTY, MINNESOTA  
CERTIFIED, FILED, AND/OR  
RECORDED ON

4/15/2013 10:53:23 AM

AS DOC #: A000591553

PAGES: 2

REC FEES: 0.00

KATHRYN M. NORBY  
CASS COUNTY RECORDER

BY SR Dep

On 12/14/2012, found a(n): 2 1/2" Iron Pipe up 1.5' in Good  
Condition.

- left monument as found
- lowered monument
- removed monument (explain)
- raised monument

On \_\_\_\_\_, set a(n): \_\_\_\_\_

See "Statement of Evidence" for further details (on back)

(reserved for recording data)

16" ASPEN  
N&D S SIDE



S 72° W  
22.41'

LOGGED AREA

S 57° E  
5.05'

3" ASPEN  
N&D SW SIDE

S 16° E  
15.10'

LOGGED AREA



10" ASPEN  
N&D W SIDE

32 | 33



### "SKETCH OF REFERENCE TIES"

(not to scale - bearings are magnetic)

Ties are measured to center of monument unless otherwise noted.

UNITS =  Metric  English

### CASS COUNTY SOUTH COORDINATES

Northing: 339302.379

Easting: 557173.013

NAD 83/2007 Adjustment.

Obtained by RTK GPS observations.

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision, and that I am a duly Licensed Land Surveyor under the laws of the State of Minnesota.

signature

3-21-13  
date

Jarrett M. Leas, Minnesota License No. 42619

Page 1 of 2 A000591553

Statement of Evidence

**East Quarter corner of Section 32, Township 139 North, Range 28 West, 5th Principal Meridian.**

- 1864 The US General Land Office, in the notes of the subdivision of Township 139 North, Range 29 West set a post for the original corner and referenced it as follows:  
10" W. Pine N 40° E 15 links 9" W. Pine N 73° W 13 links  
Said records are on file at the Minnesota Historical Society, St. Paul, Minnesota, copies are filed with the Cass County Surveyor's Office (CCSO).
- 1918 Ben Clark, RLS 231, Survey Record 434, Book C, Page 303, on file in the CCSO, a 5" square x3' Poplar post was set and witnessed by the following:  
6" Poplar N 40°30' W 26 feet 7" Poplar S 55° E 68.8 feet
- 1919 Ben Clark, RLS 231, Survey Record 434, Book C, Page 337, on file in the CCSO, indicates a 2 1/2"x4' iron pipe was set.
- 1922 Ben Clark RLS 231, Document No. 69796, on file in the CCSO, a county resurvey of sections 27, 28, 33, and 34 indicates an iron monument.
- 2012 A KLJ survey crew found a 2 1/2" iron pipe, and is witnessed with the ties shown on the front of this certificate. Jarrett Leas, RLS #42619, after analysis of record and survey information accepts this monument as the correct perpetuation of the corner.

