



A000592106

OFFICE OF THE COUNTY RECORDER
CASS COUNTY, MINNESOTA
CERTIFIED, FILED, AND/OR
RECORDED ON

5/2/2013 11:50:37 AM

AS DOC #: A000592106

PAGES: 2

REC FEES: 0.00

KATHRYN M. NORBY
CASS COUNTY RECORDER

BY SR _____ Dep

Page 1 of 2 A000592106

Index No. _____ E-13 _____

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

NORTHEAST Corner of Section 9, Township 134, Range 32

5TH Principal Meridian, State of Minnesota, County of CASS

At the corner location shown on the sketch:

On _____ found a _____
DATE

left monument as found, lowered monument, removed monument (explain)

On 5/16/11 Placed a 3/4" X 24" REBAR WITH PLASTIC CAP STAMPED "MN DNR LS 47461"
DATE
DOWN 0.5' AT THE WESTERLY EXTENSION OF CENTERLINE OF ROAD EAST



SET DNR RP UP 2'
NE SIDE 8" ASPEN
N40°W 27.86'

100TH STREET (GRAVEL)

CASS COUNTY
COORDINATE SYSTEM
NAD 83 1996 ADJ.
N = 204206.852
E = 436916.518

SET DNR RP UP 1.5'
NW SIDE 6" TWIN OAK
S30°W 75.96'

NOTE: BEARINGS OBSERVED WITH A COMPASS.

Statement of evidence for this corner location is on back of this page.

RAL - JUNE 2011
FOM01910.00.00.01

I certify that this document was researched and prepared by me or under my direct supervision.

SIGNATURE

DATE

4/24/13

License Number

47461

Title:



Land Surveyor



County Surveyor

STATEMENT OF EVIDENCE**Northeast Corner of Section 9, Township 134 North, Range 32 West, 5th P.M.**

The Department of Natural Resources, Division of Lands and Minerals, contacted the following offices for information regarding this corner:

Cass County Recorder
 Cass County Surveyor
 Cass County Highway Dept.
 Westwood Professional Services - Brainerd
 Carnell Land Surveying, LLC
 Arro of Park Rapids, LLC
 Nyberg Surveying
 Festler Land Surveying
 Kramer Leas Deleo, PC
 Widseth Smith Nolting - Baxter

1870 This corner was established by the Government Land Office. A post was set to mark the corner and was witnessed by the following bearing trees:

Tamarac	8"	S88°W	26 Links
Tamarac	5"	N73°E	192 Links

The DNR did not find any other records pertaining to this corner.

2011 In May, the DNR survey crew searched for evidence of the corner and located the centerline of a township road running east in the vicinity of the corner. No other evidence of the corner was recovered. Using the road as evidence of the corner location, the corner was computed on the westerly extension of the centerline of the road running east and proportionally between the North Quarter corner of Section 9 and the North Quarter corner of Section 10 based on the GLO survey. A ¾" x 24" rebar with cap stamped "MN DNR LS 47461" was set to mark the corner position.

North Quarter Corner Section 10 bears N89°43'09"E 2630.92'
 North Quarter Corner Section 9 bears S89°33'46'W 2618.49'

For more information on our survey in this area, please contact the MN DNR, Division of Lands and Minerals, Survey Section, 1601 Minnesota Drive, Brainerd, MN 56401

