CERTIFICATE OF LOCATION OF GOVERNMENT CORNER  Northeast   Corner of Section   19   Township   139   N   Range   27   W   5th P.M. STATE OF MINNESOTA, COUNTY OF   Cass  On   DATE   Iowered monument   Iowe	A000595688  OFFICE OF THE COUNTY RECORDER CASS COUNTY, MINNESOTA CERTIFIED, FILED, AND/OR RECORDED ON  8/22/2013 9:17:21 AM  AS DOC #: A000595688 PAGES: 2 REC FEES: 0.00 KATHRYN M. NORBY CASS COUNTY RECORDER  BY KFDep
See "Statement of Evidence" for further details (on back)	(reserved for recording data)
NW 19-139-27  NW 19-139-27  S 89'44'20" E  5067.94'  18 17  N&D SE SIDE  N&D SE SIDE  NE 6-13  NOODS  NOODS  18 17  N&D SE SIDE	8" BIRCH N&D N SIDE NE 21-139-27 S 88'59'53" E 10510.46'
	139–27
"SKETCH OF REFERENCE TIES" (not to scale — bearings are magnetic)  Ties are measured to center of monument unless otherwise noted.  UNITS = □ Metric ☑ English  I hereby certify that this survey, plan, or report was prepared by response to the survey of	CASS COUNTY SOUTH COORDINATES  Northing: 352278.362  Easting: 583279.778  NAD 83/2007 Adjustment. Obtained by RTK GPS observations.
I am a duly Licensed Land Surveyor under the laws of the State of Minnesota.	

signature

Jarrett M. Leas, Minnesota License No. 42619



Page 2 of 2 A000595688

## Statement of Evidence

## Northeast corner of Section 19, Township 139 North, Range 27 West, 5th Principal Meridian.

The US General Land Office, in notes of the subdivision of Township 139 North, Range 27 West, set a post for the original corner and referenced it as follows:

5" Oak N 55° E 10 links 7" Birch N 30° W 25 links 8" Maple S 45° E 28 links 6" Oak S 65° W 16 links

Said records are on file with the Minnesota Historical Society, St. Paul, Minnesota, copies are filed with the Cass County Surveyor's Office (CCSO).

- 1937 CCC Washburn Lake field book no. 1, page 7, on file at the DNR office in Brainerd show CCC personnel set an approximate corner post 80 chains from the west.
- KLJ field crews searched the area and found nothing. This corner was set lost by double proportion between the NE 6, NE 21, SE 31, and the NW 19. A 5/8" x 24" rebar with plastic cap stamped "Leas MN 42619" was set to mark the corner position and is witnessed with the ties shown on the front of this certificate. Jarrett Leas, RLS #42619, after analysis of record and survey information accepts this monument as the correct perpetuation of the corner.