CERTIFICATE OF LOCATIOF GOVERNMENT CORNE Northeast Corner of Section 2: Township 139 N , Range 27 W , 5th STATE OF MINNESOTA, COUNTY OF Cass On found a(n): left monument as found lowered monument compared monument (explain) raised monument compared monument (explain) Stamped "Leas MN 42619" up 1.5'. See "Statement of Evidence" for further details (on back to see "Statement of Evidence" for further details (on	A000595709 P.M. S CASS COUNTY, MINNESOTA CERTIFIED, FILED, AND/OR RECORDED ON 8/22/2013 9:17:42 AM AS DOC #: A000595709 PAGES: 2 REC FEES: 0.00 KATHRYN M. NORBY CASS COUNTY RECORDER BY KFDep
● NE 21-139-27	
NW 30-139-27 \(\sigma \ 89.18'12" \) E	4" BIRCH 199 N&D E SIDE 199 AREA LOGGED AREA
5" BIRCH N&D NW SIDE	S 89° E 6.40° 15625.84° 4" ASPEN N&D N SIDE
"SKETCH OF REFERENCE TIE (not to scale — bearings are magnetic —N— Ties are measured to center of monum unless otherwise noted. UNITS = □Metric ⊠English	Northing: 346877.587
I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision, and that I am a duly Licensed Land Surveyor under the laws of the State of Minnesota. \[\begin{align*} \delta - 3 \cdot - 201 \\ \delta \\ \de	



24 links

30 links

Page 2 of 2 A000595709

Statement of Evidence

Northeast corner of Section 28, Township 139 North, Range 27 West, 5th Principal Meridian.

The US General Land Office, in notes of the subdivision of Township 139 North, Range 27 West, set a post for the original corner and referenced it as follows:

8" Red Oak N 40° E 23 links 40" W. Pine N 30° W 8" Linn S 56° E 54 links 8" Maple S 30° W

Said records are on file with the Minnesota Historical Society, St. Paul, Minnesota, copies are filed with the Cass County Surveyor's Office (CCSO).

1937 CCC Washburn Lake field book 1, on file at the DNR office in Brainerd show CCC personnel set an approximate post 1 mile from the west. Book 2, page 24, shows at 78.44 N they found an approximate corner 1.40 chains east.

KLJ field crews searched the area and found nothing. This corner was set lost by double proportion between the NE 21, NE 25, SE 33, and the NW 30. A 5/8" x 24" rebar with plastic cap stamped "Leas MN 42619" was set to mark the corner position and is witnessed with the ties shown on the front of this certificate. Jarrett Leas, RLS #42619, after analysis of record and survey information accepts this monument as the correct perpetuation of the corner.