

Page 1 of 2 A000596608

# CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

East Quarter Corner of Section 33  
Township 138 N . Range 32 W . 5th P.M.  
STATE OF MINNESOTA, COUNTY OF CASS.



A000596608

OFFICE OF THE COUNTY RECORDER  
CASS COUNTY, MINNESOTA  
CERTIFIED, FILED, AND/OR  
RECORDED ON

9/20/2013 9:23:00 AM

AS DOC #: A000596608

PAGES: 2

REC FEES: 0.00

KATHRYN M. NORBY  
CASS COUNTY RECORDER  
BY SR Dep


On 5/12/2010 , found a(n): steel shaft  
down 0.3' on centerline of N-S Road.

- left monument as found
- lowered monument
- removed monument (explain)
- raised monument

On \_\_\_\_\_ , set a(n): \_\_\_\_\_

See "Statement of Evidence" for further details (on back)

reserved for recording data



## "SKETCH OF REFERENCE TIES" (not to scale - bearings are magnetic)

Ties are measured to center of monument unless otherwise noted.

UNITS =  Metric  English

CASS COUNTY COORDINATES, SOUTH ZONE

Northing: 306994.326

Easting: 435624.212

NAD 83, HARN 1996 Adjustment.

Obtained by RTK GPS observations.

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision, and that I am a duly Licensed Land Surveyor under the laws of the State of Minnesota

James Kramer  
signature

James Kramer, Minnesota License No. 23668

7-11-2013

Date

**Index No. 13832X.0-13.0**Statement of Evidence**East Quarter Corner of Section 33, Township 138 North, Range 32 West, 5<sup>th</sup> Principal Meridian.**

- 1870 Wood Post set to mark the corner, referenced as follows:  
6" Black Pine S 53-1/2 deg. W 64 links (42.24 feet )  
8" Black Pine N 53 deg. E 86 links (56.76 feet)  
*Said records are on file with the Secretary of State, St Paul, Minnesota, copies are filed  
With the Cass County Surveyor's Office (CCSO).*
- 2001 Cass County Surveyor crew recovered 4" curved piece of cast iron, down 0.4',  
referenced as follows:  
8" White Oak S 52 deg. E 94.12 feet  
Power Pole N 19 deg. E 121.84 feet  
Fence Post N 54 deg. W 41.75 feet
- 2010 Jarrett Leas, RLS 42619, recovered a steel shaft down 0.3', referenced as follows:  
Wood Gate Post S 69 deg. E 36.40 feet  
Power Pole N 40 deg. E 55.25 feet  
Fence Post N 54 deg. W 41.94 feet

The monument recovered, and established references for the position are shown on the face of this document.

Analysis of the recovered data, field evidence and survey measurements, indicate that the monument recovered by Jarrett Leas in 2010 is the correct perpetuation of this corner.