

# CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

East Quarter Corner of Section 34  
Township 138 N . Range 32 W . 5th P.M.  
STATE OF MINNESOTA, COUNTY OF CASS.



A000596609

OFFICE OF THE COUNTY RECORDER  
CASS COUNTY, MINNESOTA  
CERTIFIED, FILED, AND/OR  
RECORDED ON

9/20/2013 9:23:01 AM

AS DOC #: A000596609

PAGES: 2

REC FEES: 0.00

KATHRYN M. NORBY  
CASS COUNTY RECORDER

BY SR Dep


On 5/12/2010 . found a(n): 3/8" Rebar, up 0.2'

- left monument as found
- lowered monument
- removed monument (explain)
- raised monument

On \_\_\_\_\_ . set a(n): \_\_\_\_\_

See "Statement of Evidence" for further details (on back)

(reserved for recording data)



Section 34-138-32

SRP in Power Pole  
South Face up 1.0'

SRP in Power Pole  
East Face up 0.8'

Church Entrance

Punch Hole in CMP

N 86°W  
48.60'

N 09°W  
36.00'

N 37°E  
70.57'

TH 64

69' +/-

Section 35-138-32

## "SKETCH OF REFERENCE TIES" (not to scale - bearings are magnetic)



Ties are measured to center of monument unless otherwise noted.

UNITS =  Metric  English

CASS COUNTY COORDINATES, SOUTH ZONE

Northing: 307031.884

Easting: 440897.648

NAD 83, HARN 1996 Adjustment.

Obtained by RTK GPS observations.

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision, and that I am a duly Licensed Land Surveyor under the laws of the State of Minnesota

signature

7-11-2013

Date

James Kramer, Minnesota License No. 23668

Page 1 of 2 A000596609



**Index No. 13832X.0-17.0**

Statement of Evidence

**East Quarter Corner of Section 34, Township 138 North, Range 32 West, 5<sup>th</sup> Principal Meridian.**

- 1870 Wood Post set to mark the corner, referenced as follows:  
6" Black Pine S 16 deg. W 5 links (3.30 feet )  
5" Black Pine S 76 deg. E 6 links (3.96 feet)  
*Said records are on file with the Secretary of State, St Paul, Minnesota, copies are filed With the Cass County Surveyor's Office (CCSO).*
  
- 2001 MnDot survey crew recovered 3/8" rebar, up 0.2', referenced as follows:  
Power Pole NW 36.00 feet  
Power Pole SW 48.60 feet  
R/W Sign W 0.5 feet  
Hole in CMP NNE 70.5 feet
  
- 2003 Bruce Grivna, RLS 17253, indicates recovering a monument on filed Certificate of Survey.
  
- 2010 Jarrett Leas, RLS 42619, recovered a 3/8" rebar up 0.2', referenced as follows:  
Power Pole N 86 deg. W 48.60 feet  
Power Pole N 09 deg. W 36.00 feet  
Hole in CMP N 31 deg. E 70.57 feet

The monument recovered, and established references for the position are shown on the face of this document.

Analysis of the recovered data, field evidence and survey measurements, indicate that the monument recovered by Jarrett Leas in 2010 is the correct perpetuation of this corner.