

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

North Quarter Corner of Section 18
Township 138 N, Range 29 W, 5th P.M.
STATE OF MINNESOTA, COUNTY OF Cass



A000596999

OFFICE OF THE COUNTY RECORDER
CASS COUNTY, MINNESOTA
CERTIFIED, FILED, AND/OR
RECORDED ON

10/3/2013 2:30:40 PM

AS DOC #: A000596999

PAGES: 2

REC FEES: 0.00

KATHRYN M. NORBY
CASS COUNTY RECORDER

BY SR Dep

On 11/30/2012, found a(n): 1/2" Iron Pipe With Plastic Cap
Stamped "LS 17008" Down 0.2' 9'± North of 8th ST SW ☐.

- left monument as found
- removed monument (explain)
- lowered monument
- raised monument


On _____, set a(n): _____
DATE

See "Statement of Evidence" for further details (on back)

(reserved for recording data)

PINE PLANTATION

JACK PINE SNAG
N&D UP 1' SW SIDE



PRIVATE DR.
NORTH
23.31'

HOUSE

YARD

1/2" IP

8th ST SW

GRAVEL

SOUTH
24.17'

S 41° E
41.84'

JACK PINE SNAG
N&D UP 2' W SIDE




1/2" IP
RLS 43932

9" ASPEN N&D UP
1' SW SIDE

WOODS

"SKETCH OF REFERENCE TIES"

(not to scale - bearings are magnetic)



Ties are measured to center of monument unless otherwise noted.

UNITS = Metric English

CASS COUNTY SOUTH COORDINATES

Northing: 326254.431

Easting: 517532.563

NAD 83/2007 Adjustment.

Obtained by RTK GPS observations.

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision, and that I am a duly Licensed Land Surveyor under the laws of the State of Minnesota.

signature

9-30-13
date

Jarrett M. Leas, Minnesota License No. 42619

Page 1 of 2 A000596999

Statement of Evidence

North Quarter corner Section 18, Township 138 North, Range 29 West, 5th Principal Meridian.

- Aug. 1865 G.B.Wright, GLO Deputy Surveyor, in the notes of the subdivision of Township 138 North, Range 29 West set a post for the original corner and referenced it as follows:
9" N Pine N 44°30' W 389 links
Said records are on file at the Minnesota Historical Society, St. Paul, Minnesota, copies are filed with the Cass County Surveyor's Office (CCSO).
- Aug. 2004 David Landecker, RLS#17008, shows a found monument on a certificate of survey.
- Dec. 2004 Bruce Grivna, RLS#17253, shows a found monument on a certificate of survey.
- Apr. 2009 Chris Hoglund, RLS#43932, shows a found monument on a certificate of survey.
- Nov. 2012 A KLJ survey crew found a ½" Iron Pipe, and is witnessed with the ties shown on the front of this certificate. Jarrett Leas, RLS #42619, after analysis of record and survey information accepts this monument as the correct perpetuation of the corner.

